



### Overview

Presentation	Extended run power protection for servers, networks, and telecommunications
Lead time	Usually in Stock

### Main

Number of rack unit	0U
Number of cables	1.0
Battery type	Lead-Acid battery
Provided equipment	Installation guide

### Physical

Height	5.51 in (14 cm)
Width	8.27 in (21 cm)
Depth	21.50 in (54.6 cm)
Net Weight	64.15 lb(US) (29.1 kg)
Mounting Mode	Not rack-mountable
USB compatible	No

### Conformance

Product certifications	CSA
Standards	UL 1778

### Environmental

Ambient Air Temperature for Operation	32...104 °F (0...40 °C)
Operating altitude	0...10000 ft
Relative Humidity	0...95 %
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage altitude	0...15000 ft (0.00...4572.00 m)
Storage Relative Humidity	0...95 %

### Batteries & Runtime

Battery Placement	Internal Battery
Battery blocks per string	10
Battery Slots Empty	0
Included Battery Modules	0
Device mounting	Enclosed battery cartridge
Battery Voltage	120 V
RBC Quantity	1

## Ordering and shipping details

Category	11309 - APC RESALE PRODUCTS
GTIN	00731304218869
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No
Country of origin	PH

## Packing Units

Package 1 Height	15.16 in (38.5 cm)
Package 1 width	11.26 in (28.6 cm)
Package 1 Length	29.53 in (75 cm)
Number of Units in Package 3	12

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Take-back	Take-back program available

## Contractual warranty

Warranty	2 years repair or replace
----------	---------------------------