

**SKU:** CSWD-4/0-12-134

**UPC:** 0783669640571

**Features & Benefits:**

**Description:** Surecrimp Copper Compression Lug, Conductor Size 4/0, 2 Holes, 1/2in Bolt Size, 1-3/4in Hole Spacing, Standard Barrel, Sight Window, Tin Plated, UL, CSA



## Specs

### Additional Class Attributes

|                           |             |
|---------------------------|-------------|
| Barrel Marking            | Ink         |
| Barrel Type               | Standard    |
| Connecting Angle          | 180°        |
| Connection                | Compression |
| Contains DE-OX®           | No          |
| Flared End                | No          |
| ILSCOs Die Catalog Number | ILD-54      |
| ILSCOs Die Index Number   | I-54        |
| Mounting Hole Type        | Thru        |
| Narrow Tang               | No          |
| Number of Mounting Holes  | 2           |
| Sight Window              | Yes         |
| Slotted                   | No          |
| Tang End Shape            | Square      |
| Undrilled                 | No          |

### Dimensions

|                              |          |
|------------------------------|----------|
| Barrel Length (IN)           | 0.875    |
| Barrel Length (mm)           | 22.225   |
| Dimension G (IN)             | 0.546    |
| Dimension G (mm)             | 13.8684  |
| Height (IN)                  | 0.729    |
| Height BX (IN)               | 2        |
| Height (mm)                  | 18.5166  |
| Inside Diameter (IN)         | 0.546    |
| Inside Diameter (mm)         | 13.8684  |
| Length (IN)                  | 4.366    |
| Length (mm)                  | 110.8964 |
| Mounting Bolt/Stud Size (mm) | 304.8    |
| Mounting Hole Diameter (IN)  | 0.562    |
| Mounting Hole Diameter (mm)  | 14.2748  |
| Mounting Hole Spacing (IN)   | 1.75     |
| Mounting Hole Spacing (mm)   | 44.45    |
| Outside Diameter (IN)        | 0.689    |
| Outside Diameter (mm)        | 17.5006  |
| Strip Length (mm)            | 23.7998  |
| Tang Length (IN)             | 3        |
| Tang Length (mm)             | 76.2     |
| Tang Thickness (IN)          | 0.141    |

|                     |                   |
|---------------------|-------------------|
| Tang Thickness (mm) | 3.5814            |
| Tang Width (IN)     | 0.999             |
| Tang Width (mm)     | 25.3746           |
| Weight (LB)         | 0.168236737561102 |
| Weight BX (LB)      | 1.954             |
| Width (IN)          | 0.999             |
| Width BX (IN)       | 6.1875            |
| Width (mm)          | 25.3746           |

### Conductor Ranges

|  |                   |
|--|-------------------|
| Conductor Range AL Stranded (Primary, run, main, line) | NA                |
| Conductor Range CU Solid (Primary, run, main, line)    | NA                |
| Conductor Range CU Stranded (Primary, run, main, line) | 4/0 Str           |
| Conductor Range AL Solid (Primary, run, main, line)    | NA                |
| Expanded Conductor Range                               | 4/0 Str - 1 Str   |
| Flex Conductor Range                                   | 3/0 G,H,I,K,M,DLO |

### Material and Finish

|                    |        |
|--------------------|--------|
| Conductor Material | Copper |
| Connector Finish   | Tin    |
| Insulation         | NA     |
| Material           | Copper |

### Additional Technical Specifications

|                |      |
|----------------|------|
| Conductor Type | Flex |
|----------------|------|

### General

|                             |                 |
|-----------------------------|-----------------|
| Bag Quantity                | 1               |
| Carton Quantity Description | STD PACK QTY 10 |
| Direct Burial               | Yes             |
| Dual Rated                  | No              |
| NEMA Code                   | S-588-3         |
| UPC Code                    | 78366964057     |

### Bolt and Screw Sizes

|                         |     |
|-------------------------|-----|
| Mounting Bolt/Stud Size | 1/2 |
|-------------------------|-----|

### Testing Standards

|                          |   |
|--------------------------|---|
| CSA File Number          | LR-29601  |
| CSA Standard             | C22.2 No. 65-03   |
| NEBS Rating              | Level 3   |
| Prop65 Compliance        | This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation |
| ROHS Indicator           | IND   |
| UL Control Number        | 453G  |
| UL / CULUS Specification | UL 486A/B Listed  |
| UL File Number           | E6207   |

### Environment and Temperature

|                    |      |
|--------------------|------|
| Temperature Rating | 90°C |
|--------------------|------|

### Color

|            |        |
|------------|--------|
| Color      | Silver |
| Color Code | Purple |

### Voltage

|                |       |
|----------------|-------|
| Voltage Rating | 35 kV |
|----------------|-------|