



# Switch Start Metal Halide Standard

## MH175/U/M 12PK

High performance, Long life and Superior light quality A compact, energy efficient metal halide lamp that provides crisp, sparkling light with long life and high efficiency.

### Warnings and Safety

- R "WARNING: These lamps can cause serious skin burn and eye inflammation from short wave ultraviolet radiation if outer envelope of the lamp is broken or punctured. Do not use where people will remain for more than a few minutes unless adequate shielding or other safety precautions are used. Certain lamps that will automatically extinguish when the outer envelope is broken or punctured are commercially available." This lamp complies with FDA radiation performance standard 21 CFR subchapter J. (USA: 21 CFR 1040.30 Canada: SOR/DORS/80-381)
- Lamp contains mercury.
- Manage in Accord with Disposal Laws.
- See: [www.lamprecycle.org](http://www.lamprecycle.org) or 1-800-555-0050

### Product data

General information			
Base	E26 [ Single Contact Medium Screw]		1000W types must not be operated at 1500W. (377)
Operating Position	Universal [ Universal]	Footnotes HID 2	Rated life: Vertical +/- 15 degrees. Other positions 75% of vertical life. (385)
Main Application	General Lighting (G)	Footnotes HID 3	Vertical lumens. Horizontal lumens 6%–10% lower. (393)
Life to 50% Failures (Nom)	10000 h		
ANSI Code HID	M57/E		
Footnotes HID 1	Requires a ballast specified or approved for Philips metal halide lamps, or one that is designed to operate all popular brands of metal halide lamps. 1000W types will operate from H36 conventional lag type ballast for Mercury Vapor lamps at ambient temperatures of 50 degrees F or higher.		
Light technical			
Color Code	640 [ CCT of 4000K]		
Luminous Flux (Rated) (Nom)	14000 lm		
Color Designation	Cool White (CW)		
Design Mean Lumens	9100 lm		

## Switch Start Metal Halide Standard

Chromaticity Coordinate X (Nom)	0.385
Chromaticity Coordinate Y (Nom)	0.390
Correlated Color Temperature (Nom)	4000 K
Luminous Efficacy (Rated) (Min)	70 lm/W
Luminous Efficacy (rated) (Nom)	80 lm/W
Color Rendering Index (Nom)	65

### Operating and electrical

Lamp Current (Nom)	1.5 A
Ignition Supply Voltage (Min)	350 V
Re-Ignition Time (Min) (Max)	15 min
Ignition Time (Max)	120 s
Voltage (Max)	147 V
Voltage (Min)	117 V
Voltage (Nom)	132 V

### Mechanical and housing

Bulb Finish	Clear
Cap-Base Information	Brass [ Brass Cap]
Bulb Material	Hard Glass
Bulb Shape	BD17 [ BD17]

### Approval and application

Energy Saving Product	Not Applicable
-----------------------	----------------

Mercury (Hg) Content (Max)	24.0 mg
----------------------------	---------

### UV


Pet (Niosh) (Nom)	147.03 h/500lx
Damage Factor D/fc (Nom)	0.42

### Luminaire design requirements


Bulb Temperature (Max)	450 °C
Cap-Base Temperature (Max)	210 °C

### Product data

Order product name	MH175/U/M 12PK
EAN/UPC - Product	046677114169
Order code	313585
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	12
Material Nr. (12NC)	928601122311
Net Weight (Piece)	0.001 kg



## Dimensional drawing



MH175/U/M 12PK

Product	D	C (max)
MH175/U/M 12PK	2.125 in	5.438 in

