

DESCRIPTION

Recessed 3.5" aperture downlight luminaire utilizing a LED array. Housing is air tight and suitable for 2x8 residential or commercial constructions. Insulation must be kept 3" from top and sides on housing. Housing platform + primary reflector + optical element combination supports various distributions and reflector types providing design flexibility. Use where excellent light control and low aperture brightness are demanded.

Catalog #		Type
Project		
Comments		Date
Prepared By		

SPECIFICATION FEATURES

Frame

Galvanized steel plaster frame with integral bar hanger receivers. Setscrews provide positive horizontal locking. Integral gun sights facilitate the use of guide strings or laser lines. Shipped with overspray protector installed.

Housing

Steel housing painted matte black for visually dark interior. Removable access panels allow splice inspection and service of all electrical components including LED module and driver from below the ceiling thru the aperture. Removable hinged top allow top access. All fasteners are captive.

Bar Hangers

Captive preinstalled bar hangers adjust from 8-1/2" to 24" wide; pass thru feature allows shortening without removal. Captive nail penetrates standard and engineered lumber. Mounting flange levels platform with ceiling. Integral clip attached directly to tee-bar.

Universal Mounting Bracket

Accepts 1/2" EMT, C channel and bar hangers and adjusts 3" vertically from above the ceiling.

Gaskets

Closed cell gaskets achieve restrictive airflow requirements without additional caulking.

Adjustment Mechanism

Dynamic aiming rotates 365°, tilts 45° and locks in position. Angle markings assist in repeatable settings. Translating center beam optics aligns axis of primary reflector with aperture from nadir to 45°.

LED Module

Field replaceable module utilizes Cree® MT-G2 LED array and conforms to Zhaga standards for interchangeability. Proximity phosphors over chip on board LEDs provide a uniform source with high efficiency and no pixilation. Color accuracy within 2 SDCM and optional 90 CRI provides excellent color. Passive cooling achieves L70 at 40,000 hours.

Primary Optic

Borosilicate glass segmented optic with > 95% reflective multi-layer hard coating delivers a highly efficient and uniform beam. Various distributions are available and can be interchanged without tools. Elastomeric glare shield accepts theatrical color filters and diffusion films.

Media

Optional media holder accepts one or two 2 inch [50mm] diameter L series color filters or beam modifying lens. Order media holder, color filters and lens separately.

Lower Reflector

Spun 0.04" thick high purity aluminum parabolic contour provides 50° lamp and lamp image cutoff and is available in a wide range of specular and semi-specular Alzak® finishes. Light trap eliminates spill light at edge of flange and reflector. Metal trim ring can be removed for painting and can be installed flush mount with optional flush mount collar accessory.

Trim Retention

Retained with two torsion springs holding the flange tightly to the finished ceiling surface and accommodates ceiling thickness from 1/2 - 1" thick. Use optional plaster lip

extender for ceilings up to 2" thick.

Junction Box

(6) 1/2" and (2) 3/4" trade size pry outs positioned to allow straight conduit runs.

Driver


Integral constant current driver provides noise free operation. Continuous, flicker-free 1% dimming, available with 2 or 3 wire phase cut and EcoSystem/DALI digital control interfaces. The DALI option is Fifth Light compatible.

Compliance

Type Non-IC inherently protected and cULus listed for damp locations. Insulation must be kept 3" from top and sides on housing. Restrictive airflow per ASTM-E283. EMI/RFI emissions per FCC 47CFR Part 18 consumer limits. Contains no mercury or lead and RoHS compliant. Photometric testing in accordance with IES LM-79-08. Lumen maintenance projections in accordance with IES LM-80-08 and TM-21-11. Meets California Title 24 residential fixture program and listed on appliance database. Energy Star listed. Zhaga compliant. Meets EMI/RFI emission per FCC 47CFR Part 18 consumer limits at 120V input. Lighting Facts Labeled.



Warranty

5 year warranty.



**PN3LED12
E3MR**

**LED Downlight
3.5" Aperture
1,200 Lumen Series**



E Driver Option		
Input Voltage	120V	277V
Input Current (A)	0.16	0.08
Input Power (W)	19.5	20
Inrush Current (A)	0.24	0.5
THD: ≤ 20%		
PF: ≥ 0.90		
T Ambient: -20 to +40°C		
T Plenum: +65°C Max.		
Sound Rating: Class A		
E010 Driver Option		
Input Voltage	120V	277V
Input Current (A)	0.17	0.08
Input Power (W)	20	20.7
Inrush Current (A)	0.7	1.21
THD: ≤ 20%		
PF: ≥ 0.90		
T Ambient: -20 to +40°C		
T Plenum: +65°C Max.		
Sound Rating: Class A		



Zhaga powered by **fifthlight**
Cooper Lighting Solutions is a founding member of the Zhaga Consortium

ORDERING INFORMATION

PN3LED E3MR

Complete luminaire consists of a housing platform and optical element. Housing platform can be ordered without primary optic. Order primary optics separately.

Example: PN3LED12830E RG50FL40 E3MRH

Platform	Lumens ¹	Distribution	Color	Driver
PN3LED				
PN3LED = 3.5" Aperture Non-IC, AT LED Housing Platform	12 = 1,200 Lumens (Nominal)	[Blank] = Omit Primary Optic NSP10 = 10° Beam SP15 = 15° Beam NFL25 = 25° Beam FL40 = 40° Beam	827 = 80 CRI Minimum, 2,700 K CCT 927 = 90 CRI Minimum, 2,700 K CCT 830 = 80 CRI Minimum, 3,000 K CCT 930 = 90 CRI Minimum, 3,000 K CCT 835 = 80 CRI Minimum, 3,500 K CCT 840 = 80 CRI Minimum, 4,000 K CCT	E = 120 – 277V 50/60Hz Leading or Trailing Edge Phase Cut 1% Dimming (phase cut dimming at 120V only) E010 = 120 – 277V 50/60Hz 0 -10V 10% Dimming ED010 = 120 – 277V 50/60Hz 0 -10V 1% Dimming E5LT = 120 – 277V 50/60Hz DALI 1% Dimming EDMX = 120 – 277V 50/60Hz DMX 1% Dimming 1ELTE = 120V 60Hz Leading Edge 1% Dimming, Lutron A-Series EL3D = 120 – 277V 50/60Hz 3-wire and EcoSystem 1% Dimming, Lutron A-Series

Optical Element	Finishes	Options	Accessories
E3MR			
E3MR = 3.5" Aperture Open Downlight Reflector	Alzak® Finishes C = Specular Clear H = Semi-Specular Clear G = Gold WMH = Warm Haze WH = Wheat WHH = Wheat Haze GP = Graphite GPH = Graphite Haze K = Cognac KH = Cognac Haze CC = Chocolate CCH = Chocolate Haze B = Black	Painted Finishes MW = Matte white W = Gloss white BB = Black baffle WB = White baffle	[Blank] = Metal Trim Ring, Matte White Not available with BB or WB SF = Self-flanged SFWF = Self-flanged, Matte White Flange
			RG50NSP10 = 10° Beam Glass Reflector, 50mm RG50SP15 = 15° Beam Glass Reflector, 50mm RG50NFL25 = 25° Beam Glass Reflector, 50mm RG50FL40 = 40° Beam Glass Reflector, 50mm RG50MH = Media Holder for two inch [50mm] diameter L series color filters or beam modifying lens. Attaches directly to RG50 series 50mm Reflectors FMC3 = Flush Mount Collar Accessory PLE3 = Plaster Lip Extender for Up to 2" Thick Ceilings ZLM03 = Replacement LED module, see specification sheet for catalog number and performance data

ENERGY DATA

PN3LED E3MR

1ELTE Driver Option		EL3D Driver Option		E5LT Driver Option		EDMX Driver Option	
Input Voltage	120V 277V	Input Voltage	120V 277V	Input Voltage	120V 277V	Input Voltage	120V 277V
Input Current (A)	0.17	Input Current (A)	0.16 0.08	Input Current (A)	0.17 0.08	Input Current (A)	0.17 0.08
Input Power (W)	20.1	Input Power (W)	19.2 19.8	Input Power (W)	19.5 20.2	Input Power (W)	20 21.3
Inrush Current (A)	1.9	Inrush Current (A)	1.9 2	Inrush Current (A)	1.73 1.8	Inrush Current (A)	1.82 1.89
THD: ≤ 20%		THD: ≤ 20%		THD: ≤ 20%		THD: ≤ 20%	
PF: ≥ 0.90		PF	≥0.90 ≥0.85	PF	≥0.90 ≥0.85	PF	≥0.90 ≥0.70
T Ambient: -20 to +40°C		T Ambient: -20 to +40°C		T Ambient: -20 to +40°C		T Ambient: -20 to +40°C	
T Plenum: +65°C Max.		T Plenum: +65°C Max.		T Plenum: +65°C Max.		T Plenum: +65°C Max.	
Sound Rating: Class A		Sound Rating: Class A		Sound Rating: Class A		Sound Rating: Class A	

LIGHTING FACTS

Lighting Facts
A Program of the U.S. DOE

Light Output (Lumens) **1152**
Watts **18.5**
Lumens per Watt (Efficacy) **62**

Color Accuracy **80**
Color Rendering Index (CRI)

Light Color **3000 (Bright White)**
Correlated Color Temperature (CCT)


Warm White 2700K 3000K Bright White 4000K Daylight 6500K

All results are according to IEEE/ANSI LM-79-2008: Approved Method for the Electrical and Photometric Testing of Solid-State Lighting. The U.S. Department of Energy (DOE) verifies product test data and results.


Visit www.lightingfacts.com for the Label Reference Guide.

Registration Number: F423-APR19A (10/11/2013)
Model Number: PN3LED12FL25830E E3MR3C 2P 9H
Type: Luminaire - Downlight

Please see LightingFacts.com for a complete listing of products.




Test Number	P108684
Platform	PN3LED12830E
Element	E3MRC RG50FL40
Lumens	1136 Lm
Efficacy	61.1 Lm/W




ZONAL LUMEN SUMMARY		
Zone	Lumens	%Fixture
0-30	1055	92.9
0-40	1134	99.8
0-60	1135	99.9
0-90	1136	100
90-180	0	0
0-180	1136	100


CONE OF LIGHT



MH	FC	L	W
5.5'	81.1	3.6	3.6
7'	50.1	4.6	4.6
8'	38.4	5.4	5.4
9'	30.3	6	6
10'	24.5	6.8	6.8
12'	17	8.2	8.2




Test Number	P108702
Platform	PN3LED12830E
Element	E3MRC RG50NFL25
Lumens	1152 Lm
Efficacy	62.3 Lm/W




ZONAL LUMEN SUMMARY		
Zone	Lumens	%Fixture
0-30	1146	99.5
0-40	1151	99.9
0-60	1152	100
0-90	1152	100
90-180	0	0
0-180	1152	100


CONE OF LIGHT



MH	FC	L	W
5.5'	144.8	2.6	2.6
7'	89.4	3.2	3.2
8'	68.4	3.8	3.8
9'	54.1	4.2	4.2
10'	43.8	4.6	4.6
12'	30.4	5.6	5.6




Test Number	P108708
Platform	PN3LED12830E
Element	E3MRC RG50SP15
Lumens	1340 Lm
Efficacy	72.4 Lm/W




ZONAL LUMEN SUMMARY		
Zone	Lumens	%Fixture
0-30	1313	98
0-40	1321	98.5
0-60	1330	99.2
0-90	1340	100
90-180	0	0
0-180	1340	100


CONE OF LIGHT



MH	FC	L	W
5.5'	265	1.8	1.8
7'	163.6	2.4	2.4
8'	125.3	2.6	2.6
9'	99	3	3
10'	80.2	3.4	3.4
12'	55.7	4	4




Test Number	P108714
Platform	PN3LED12830E
Element	E3MRC RG50NSP10
Lumens	1249 Lm
Efficacy	67.5 Lm/W



ZONAL LUMEN SUMMARY		
Zone	Lumens	%Fixture
0-30	1229	98.3
0-40	1235	98.8
0-60	1241	99.3
0-90	1251	100.1
90-180	-2	-0.1
0-180	1249	100

CONE OF LIGHT



MH	FC	L	W
5.5'	314.6	1.2	1.2
7'	194.2	1.6	1.6
8'	148.7	2	2
9'	117.5	2.2	2.2
10'	95.2	2.4	2.4
12'	66.1	3	3