



**SKU:** GBT-1/0

**UPC:** 0783669000719

**Features & Benefits:**

**Description:** Aluminum Intersystem Ground Tap, Dual Rated, Main Conductor Range 1/0-8, Tap Range 2-14, UL, CSA

## Specs

### Additional Class Attributes

Connection	Mechanical
Mounting Hole Type	NA
Number of Conductors	1
Number of Ports / Wireways	1
Wire Orientation	Perpendicular

### Dimensions

Height (IN)	1.16
Height BX (IN)	2.25
Length (IN)	2.25
Weight (LB)	0.217
Weight BX (LB)	2.2021
Width (IN)	1.125
Width BX (IN)	5

### Material and Finish

Conductor Material	Copper
Connector Finish	NA
Enclosure Material	NA
Insulation	NA
Material	Aluminum
Wire Binding Hardware Material	Stainless steel

### Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

### General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 6
Direct Burial	Yes
Dual Rated	Yes
NEMA Code	S-573-2
UPC Code	78366900071

### Bolt and Screw Sizes

Mounting Bolt/Stud Size

NA

### Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	667P
UL / CULUS Specification	UL 467 Listed
UL File Number	E34440

### Color

Color

Silver

### Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	2 Sol - 14 Sol
Conductor Range AL Stranded (Primary, run, main, line)	1/0 Str - 8 Str
Conductor Range AL Stranded (Secondary, tap, load)	2 Str - 14 Str
Conductor Range CU Solid (Primary, run, main, line)	1/0 Sol - 8 Sol
Conductor Range CU Solid (Secondary, tap, load)	2 Sol - 14 Sol
Conductor Range CU Stranded (Primary, run, main, line)	1/0 Str - 8 Str
Conductor Range CU Stranded (Secondary, tap, load)	2 Str - 14 Str
Conductor Range AL Solid (Primary, run, main, line)	1/0 Sol - 8 Sol