



# PL-C Cluster 4-Pin Base

## PL-C 26W/841/4P/ALTO 10PK

Philips Linear Compact Fluorescent Lamps offer designers, specifiers and end-users new levels of efficiencies and versatility in sizes, configurations and application possibilities. With so many elegant fixtures available to complement their small size, high light output and advanced technology, Philips Energy Advantage lamps are fast becoming the preferred choice when maximum efficiency and sleek design solutions are required.

### Warnings and Safety

- Lamp contains mercury.
- Manage in Accord with Disposal Laws.
- See: [www.lamprecycle.org](http://www.lamprecycle.org) or 1-800-555-0050

### Product data

General information	
Base	G24Q-3 [ G24q-3]
Life to 50% Failures Preheat (Nom)	13000 h
LSF Preheat 2000 h Rated	99 %
LSF Preheat 4000 h Rated	98 %
LSF Preheat 6000 h Rated	97 %
LSF Preheat 8000 h Rated	90 %

Light technical	
Color Code	841 [ CCT of 4100K]
Initial lumen (Nom)	1800 lm
Luminous Flux (Rated) (Nom)	1800 lm
Color Designation	Cool White (CW)
Correlated Color Temperature (Nom)	4100 K

Luminous Efficacy (rated) (Nom)	67 lm/W
Color Rendering Index (Nom)	82
LLMF 2000 h Rated	92 %
LLMF 4000 h Rated	87 %
LLMF 6000 h Rated	83 %
LLMF 8000 h Rated	81 %

Operating and electrical	
Power (Rated) (Nom)	26.0 W
Lamp Current (Nom)	0.335 A

Temperature	
Design Temperature (Nom)	28 °C

## PL-C Cluster 4-Pin Base

### Controls and dimming

Dimmable	Yes
----------	-----

### Mechanical and housing

Cap-Base Information	4P
----------------------	----


### Approval and application

Mercury (Hg) Content (Nom)	1.4 mg
Energy Consumption kWh/1000 h	29 kWh


### Product data

Order product name	PL-C 26W/41/4P/ALTO 10PK
--------------------	--------------------------

EAN/UPC - Product	046677111779
Order code	383372
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	927907384030
Net Weight (Piece)	60.400 g
ILCOS Code	FSQ-26/40/1B-E-G24q=3




## Dimensional drawing




PL-C 26W/41/4P/ALTO 10PK

Product	D (max)	D1 (max)	A (max)	B (max)	C (max)
PL-C 26W/41/4P/ALTO 10PK	27.1 mm	27.1 mm	130.5 mm	149.0 mm	163.9 mm

## Photometric data





LDPB\_PLC4P\_840-Spectral power distribution B/W



LDPO\_PLC4P\_840-Spectral power distribution Colour


# PL-C Cluster 4-Pin Base

## Lifetime



LDLE\_PLC4P\_0001-Life expectancy diagram

LDLE\_PLC4P\_0002-Life expectancy diagram



LDLM\_PLC4P\_0001-Lumen maintenance diagram

