


ATKORE SMART-NUT™ FOR THREADED RODS



Installation



Snap-on
Rod



Adjust
Up/Down



Insert
Through Strut



1/4
Turn



Smart-Nut
Locked

Key Features

- Labor Savings, no threading required
- Quickly installed and removed
- High strength yield
- To be used with $\frac{3}{16}$ " x $1\frac{1}{8}$ " Strut holes
- Simplifies multiple levels of trapeze installation
- Made in the USA

Specifications

Material	Iron, Spring Steel Band
Finish	Zinc Electroplate Trivalent
Color	12 Gauge Silver, 14 Gauge Gold
Application	Slotted Trapeze

Part Number	Gauge	Thread	Spring Band	A Head Width	B Height	C Width	D Length	Install A Max Recommended Load 3x Safety Factor	Install B Max Recommended Load 3x Safety Factor
P3018-1420EG	14	1/4"-20	Gold					450 lbs	350 lbs
P3018-3816EG	14	3/8"-16	Gold	12mm (0.472in)	25.92mm (1.020in)	20.0mm (0.787in)	22.0mm (0.866in)	450 lbs	350 lbs
P3019-1420EG	12	1/4"-20	Silver					800 lbs	600 lbs
P3019-3816EG	12	3/8"-16	Silver					800 lbs	600 lbs



For more info visit [atkore.com/unistrut](https://www.atkore.com/unistrut)

