

STAINLESS STEEL FLEX STRAIGHT CONNECTORS

Features:

- Manufactured in type 316 stainless steel for increased corrosion resistance
- Excellent strength and durability
- Polished with standard “brite” finish to increase corrosion resistance and aesthetic appearance
- Approved for damp locations when used with Calbrite’s PVC and Clear Coated flex conduit
- Neoprene O-ring and type 316 stainless steel Locknut included
- NPT threads
- No package qty. required

Certifications and Compliances:


- NEMA 4X approved
- Temperature Ratings:
 - Stainless steel body -approx. 1700°F
 - Internal insulated throat (gray) - approx. 350°F
 - Internal plastic ferrule (white) - approx. 450°F
 - Neoprene O-ring - approx. 600°F



Applications:

Used to connect stainless flexible conduit to other fittings. Assists in preventing contamination of oils, dirt, dust, and liquid when used with Calbrite PVC coated stainless flexible conduit. Flexible stainless steel conduit can be used for protecting electronic and electrical wires and cable. Suitable for corrosive environments, including pumps, motors, HVAC systems, machine tools, electrical housings and cabinetry.

Part Number	Size (in)	A (in)	B (in)	Weight each per (lb)
S60500FCSO	½	1.560	1.250	1.950
S60700FCSO	¾	1.610	1.540	2.290
S61000FCSO	1	1.810	1.860	2.850
S61200FCSO	1 ¼	2.000	2.250	3.150
S61500FCSO	1 ½	2.175	2.650	3.750
S62000FCSO	2	2.360	3.210	4.500



All dimensions are for informational purposes only *Tolerances +/- 5%



For more info visit atkore.com/calbrite

