

**SKU:** CLWS-1-516

**UPC:** 0783669634358

**Features & Benefits:**

**Description:** Surecrimp Copper Compression Lug, Conductor Size 1, 1 Hole, 5/16in Bolt Size, Long Barrel, Sight Window, Tin Plated, UL, CSA



## Specs

### Additional Class Attributes

Barrel Marking	Ink
Barrel Type	Long
Connecting Angle	180°
Connection	Compression
Contains DE-OX®	No
Flared End	No
ILSCOs Die Catalog Number	ILD-37
ILSCOs Die Index Number	I-37
Mounting Hole Type	Thru
Narrow Tang	No
Number of Mounting Holes	1
Sight Window	Yes
Slotted	No
Tang End Shape	Square
Undrilled	No

### Dimensions

Barrel Length (IN)	1.375
Barrel Length (mm)	34.925
Dimension G (IN)	0.352
Dimension G (mm)	8.9408
Height (IN)	0.504
Height BX (IN)	2.25
Height (mm)	12.8016
Inside Diameter (IN)	0.359
Inside Diameter (mm)	9.1186
Length (IN)	2.58
Length (mm)	65.532
Mounting Hole Diameter (IN)	0.343
Mounting Hole Diameter (mm)	8.7122
Mounting Hole Spacing (mm)	0
Outside Diameter (IN)	0.469
Outside Diameter (mm)	11.9126
Strip Length (mm)	36.4998
Tang Length (IN)	0.875
Tang Length (mm)	22.225
Tang Thickness (IN)	0.109
Tang Thickness (mm)	2.7686
Tang Width (IN)	0.673

Tang Width (mm)	17.0942
Weight (LB)	0.0554315215694995
Weight BX (LB)	1.456
Width (IN)	0.673
Width BX (IN)	5
Width (mm)	17.0942

### Conductor Ranges

Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Stranded (Primary, run, main, line)	1 Str
Conductor Range AL Solid (Primary, run, main, line)	NA
Expanded Conductor Range	1 Str - 6 Str
Flex Conductor Range	2 G,H,I,K,M,DLO

### Material and Finish

Conductor Material	Copper
Connector Finish	Tin
Insulation	NA
Material	Copper

### Additional Technical Specifications

Conductor Type	Stranded
----------------	----------

### General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 10
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-588-3
UPC Code	78366963435

### Bolt and Screw Sizes

Mounting Bolt/Stud Size	5/16
-------------------------	------

### Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
NEBS Rating	Level 3
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 467 Listed
UL File Number	E6207

### Environment and Temperature

Temperature Rating	90°C
--------------------	------

**Color**

<b>Color</b>	Silver
<b>Color Code</b>	Green

**Voltage**

<b>Voltage Rating</b>	35 kV
-----------------------	-------