



D2GF1-KW

15 Amp, Self Test, Tamper-Resistant Smart GFCI Outlet with LED Indicator Light

15A, 125V, 20A Feed-Through, Wi-Fi® Certified Smart GFCI Receptacle/Outlet - White Only

An industry first! Our Smart GFCI Outlet provides peace of mind by sending notifications directly to your smart phone when a GFCI trips due to a ground-fault, using the My Leviton app. At a glance, the app provides details on protection status, if a ground-fault occurs, and if the GFCI is in test mode; (for safety) the app does not provide on/off control. Through the My Leviton app, users will know exactly which Smart GFCI in their home has tripped.

Color : White

UPC Code : 078477333662

Country Of Origin : China

NEMA :  5-15R

- An upgrade to Leviton's GFCI Outlet with Audible Trip Alert, allowing you to receive notifications and alerts wherever you are via the My Leviton app.
- Ideal for refrigerators, sump pumps, and other appliances in out-of-the-way locations such as a garage or basement. Also great for second homes and other remote locations where daily visual checks are unlikely.
- Includes an optional audible alarm that can be enabled or silenced. It is a perfect complement to Leviton's Decora Smart® product line and can be combined with other My Leviton-enabled devices to build a whole home smart solution reflective of today's connected lifestyle.
- Provides continuous ground-fault protection and meets latest UL requirements.
- Patented Reset Lockout feature prevents reset if the GFCI is not wired or operating correctly.
- Available in 20 Amp [here](#)

[Learn more about the My Leviton app](#)

Technical Information

Product Features

Amperage : 15 A

At Rated Voltage : 1 HP

Brand : SmartlockPro

Color : White

Feature : Self-Test

Fed Spec WC-596 : Yes

Grade : Residential
/Commercial Specification
Grade

Grounding : Self Grounding

NEMA : 5-15R

Pole : 2

Smart : Yes

AC Horsepower Ratings

At Rated Voltage : 1 HP

Dielectric Voltage :
Withstands 1250VAC per UL
943

Short Circuit Current Rating :
10KA

Temperature Rise : Max 30C
after 100 cycles OL at 150
percent rated current

Standards and Certifications

: Meets the latest UL requirements cULus Listed UL Standard 943 Class A (GFCI) and 498 (Receptacles) UL Listed (File #E48380) NOM Certified Meets Federal Specification W-C-596G

Strap Material : Galvanized Steel

Tamper Resistant : Yes

Termination : Back & Side

Trip Level : Class A, 5mA plus or minus 1mA

Type : Wi-Fi

Voltage : 125 VAC

Wallplate : Not Included

Warranty : 2-Year Limited

Wire : 3

Electrical Specifications

Dielectric Voltage : Withstands 1250VAC per UL 943

Flammability : Rated V-2 per UL 94

Operating Temperature : -35C to +66C

Short Circuit Current Rating : 10KA

Temperature Rise : Max 30C after 100 cycles OL at 150 percent rated current

Environmental Specifications

Body Material : Polycarbonate

Clamps : Brass

Face Material : Thermoplastic

Grounding Screw : Plated Steel

Line Contacts : Brass Double Wipe .031 Thick

Notes : Wallplate Sold Separately

Operating Temperature : -35C to +66C

Terminal Screws : Plated Steel

Yoke : Zinc-Plated Steel

Material Specifications

Body Material : Polycarbonate

Clamps : Brass

Face Material : Thermoplastic

Grounding Screw : Plated Steel

Line Contacts : Brass Double Wipe .031 Thick

Notes : Wallplate Sold Separately

Product ID : Ratings are permanently marked on device

Terminal Accom. : 14-10 AWG

Mechanical Specifications

Amperage : 15 A

Body Material : Polycarbonate

Brand : SmartlockPro

Color : White

Face Material : Thermoplastic

Feature : Self-Test

Fed Spec WC-596 : Yes

Grade : Residential /Commercial Specification Grade

Grounding : Self Grounding

NEMA : 5-15R

Terminal ID : Brass-Hot,
Green-Ground, Silver-Neutral

Terminal Screws : Plated Steel

Yoke : Zinc-Plated Steel

Pole : 2

Product ID : Ratings are
permanently marked on device

Standards and Certifications
: Meets the latest UL
requirements cULus Listed UL
Standard 943 Class A (GFCI)
and 498 (Receptacles) UL
Listed (File #E48380) NOM
Certified Meets Federal
Specification W-C-596G

Strap Material : Galvanized
Steel

Tamper Resistant : Yes

Terminal Accom. : 14-10 AWG

Terminal ID : Brass-Hot,
Green-Ground, Silver-Neutral

Termination : Back & Side

Torque Range : 14 – 18 in.-lbs

Trip Level : Class A, 5mA plus
or minus 1mA

Type : Wi-Fi

Voltage : 125 VAC

Warranty : 2-Year Limited

Wire : 3

Standards and Certifications

Fed Spec WC-596 : Yes

NOM Certified : Yes

UL 498 : Yes

UL 943 : Yes

UL Listed : File #E48380

cULus : Yes

Features and Benefits

- Sends notifications via the My Leviton app when a trip occurs due to a ground-fault
- Provides protection status via the My Leviton app
- Provides continuous ground-fault protection, detects and trips on actual ground-fault even when self-test is being conducted
- Includes an optional audible alarm that can be enabled or silenced via the My Leviton app
- Patented Reset Lockout prevents reset if the GFCI is not wired or operating correctly
- Status LED provides simple, intuitive feedback on power, protection, and connectivity status as well as indication of line/load reversal (a common wiring mistake)
- Tamper-Resistant shutters help prevent the insertion of unintended foreign objects

- _ Terminals allow for easy wiring options – back and side wire capable
- External back wire clamps provide visual indication of proper wire seating
- Advanced electronics design provides superior resistance to electrical surges and over-voltages
- Compatible with all Decora devices and wallplates (sold separately)
- For indoor use only

SPECIFICATION SUBMITTAL

JOB NAME: <input style="width: 95%; height: 20px;" type="text"/>	CATALOG NUMBERS: <input style="width: 45%; height: 20px;" type="text"/> <input style="width: 45%; height: 20px;" type="text"/>	
JOB NUMBER: <input style="width: 95%; height: 20px;" type="text"/>	<input style="width: 45%; height: 20px;" type="text"/> <input style="width: 45%; height: 20px;" type="text"/>	

Leviton Manufacturing Co., Inc

201 North Service Road, Melville, NY 11747

Telephone: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S. T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52) 5386- 1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2024 Leviton Manufacturing Co., Inc. All Rights Reserved. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts

© 2024 Leviton Manufacturing Co., Inc.