

Rittal – The System.

Faster – better – everywhere.



WM 8018.630

WM wall-mounted disconnect enclosure

State: 9/22/2025 (Source: rittal.com/us-en)

ENCLOSURES

POWER DISTRIBUTION

CLIMATE CONTROL

IT INFRASTRUCTURE


SOFTWARE & SERVICES

FRIEDHELM LOH GROUP



WM 8018.630 - WM wall-mounted disconnect enclosure 304 stainless steel

These flange mount disconnect wallmount enclosures can be used for virtually any application. The WM series ensures NEMA protection through a secure locking system, foamed-in-place gasket, and knife-edge sealing surface. Features include a stainless steel body and door, and a zinc plated mounting panel.



Features

| | |
|--------------------------------------|--|
| Model No. | WM 8018.630 |
| Material | Door: Stainless steel, all-round foamed-in PU seal Housing and door: Stainless steel 1.4301 (AISI 304) Mounting plate: Carbon steel, zinc-plated |
| Surface finish | Brushed |
| Supply includes | Housing with door Door hinged on left Wall mounting blind-nuts Flange door with universal disconnect cutout |
| Dimensions | Width: 975 mm Height: 1,200 mm Depth: 300 mm Width: 38.4 " Height: 47.2 " Depth: 11.8 " |
| Dimensions of mounting plate (W x H) | 840 mm x 1,155 mm 33.1 " x 45.5 " |
| Protection category NEMA | NEMA 4X |

Features

| | |
|-------------------------------------|----------------|
| Material thickness - door | 2 mm 0.08 " |
| Material thickness - enclosure | 2 mm 0.08 " |
| Material thickness – mounting plate | 3 mm 0.12 " |
| Packaging unit | 1 pc(s). |
| Net weight | 41.887 |
| Gross weight | 191.001 |
| Customs tariff number | 7326909099 |
| UPC-Code | 83948 |

Approvals

| | |
|--------------|---------------------------|
| Explanations | Declaration of conformity |
|--------------|---------------------------|