Powering Business Worldwide

pe.eaton.com

Eaton Bussmann series high speed cylindrical fuse

FWX-10A14F

UPC:051712795555

Dimensions:

- **Height:** 10 MM
- **Length:** 38 MM
- **Width:** 10 MM

Weight:22.4 G

Warranties:

- Not Applicable

Specifications:

- **Type:** Fuse
- **Application:** protection of DC common bus, DC drives, power converters/rectifiers and reduced voltage starters
- **Voltage Rating Numeric:** 250 V
- **Amperage Rating:** 10A
- **Amperage Rating Numeric:** 10 A
- **Interrupt Rating:** 200 kAIC Vac, 50 kAIC at 250 Vdc
- **Connection:** Ferrule end X ferrule end
- **Construction Size:** 14 x 51 mm
- **Packaging Type:** Standard
- **Breaking Capacity:** 200 A
- **Clearing (I2T):** Clearing at 250V: 24
- **Frequency Rating Maximum:** 62 HZ
- **Frequency Rating Minimum:** 45 HZ
- **Fuse Shape:** cylindrical
- **Fuse Indicator:** Non Indicating
- **Pre Arc (I2T):** 3.6
- **Release Characteristic:** Other
- **Utilization category:** aR (accompanied semiconductor protection)
- **Voltage Type:** AC/DC

- **Watt Losses:** 3.4W
- **With Striker:** No

Supporting documents:

- Product Catalog
- 250V 10AMP S/COND FERRULE 14.3 X 50.8MM

Certifications:

- UL Recognized

Product compliance:

- CE Marked

© 2016 Eaton. All rights reserved.