



Vinyl Splice For 16 - 14 AWG

By Burndy
Catalog # [SP14BG25](#)



Electrolytic Copper Butt Splice, 16 - 14 AWG, 600 V, Tin Plated.

Application

For Accommodating A Broad Range Of 600 Volt Cables

General

Color Code	Blue
Connector Type	Seamless Butt Splice
EU RoHS Indicator	Yes
Feature - Barrel Style	Shrouded
Insulation	Y
Insulation Type	Vinyl
Material	Copper
Plated	Y
Plating Type	Tin
Sub Brand	HYDENT
Temperature Rating	105° C
Trade Name	VINYLINK™
Type	SP
UPC	781810486290
UPC 12 Digit	7818104862900

Dimensions

Dimension - Diameter Max Size inch	0.18 in
Dimension - Length Overall inch	1.00 in
Dimension - Strip Length inch	1/4 in

Electrical Ratings

Voltage - Maximum	600 V
-------------------	-------

Conductor Related

Conductor - Copper Solid Size	16 AWG;15 AWG;14 AWG
Conductor - Copper Solid Size Range	16 AWG-14 AWG
Conductor - Copper Str Size	16 AWG;14 AWG
Conductor - Copper Str Size Range	16 - 14 AWG
Conductor Size	16 - 14 AWG

Certifications and Compliance

Certification - CSA Approved	Yes
Certification - ETL	No
Certification - UL Recognized	No
Certification - cULus	No
Industry Standard(s)	UL467
Standards - Industry Standards Met	UL486
Standards - RoHS Compliance Status	CM
UL Listed	Yes

Logistics

Minimum Pack Quantity	5
-----------------------	---

Product Assets

[Catalogs - Full Line BURNDY Catalog](#)
[Sales Drawings - 10104489](#)



A proud member of the Hubbell Family.