



**SKU:** AK-4/0

**UPC:** 0783669008357

**Features & Benefits:**

**Description:** Aluminum Split Bolt, Main Range 4/0-2, Tap Range 4/0-6, Tin Plated, UL, CSA

## Specs

### Additional Class Attributes

|                      |            |
|----------------------|------------|
| Connection           | Mechanical |
| Number of Conductors | 1          |
| Number of Poles      | 1          |

### Dimensions

|                 |              |
|-----------------|--------------|
| Drive Size Main | 1-1/2        |
| Drive Type Main | External Hex |
| Height (IN)     | 1.13         |
| Height BX (IN)  | 2.75         |
| Length (IN)     | 2.54         |
| Weight (LB)     | 0.2375       |
| Weight BX (LB)  | 6.249        |
| Width (IN)      | 1.49         |
| Width BX (IN)   | 6            |

### Material and Finish

|                    |          |
|--------------------|----------|
| Conductor Material | Aluminum |
| Connector Finish   | Tin      |
| Insulation         | NA       |
| Material           | Aluminum |

### Additional Technical Specifications

|                |          |
|----------------|----------|
| Conductor Type | Stranded |
|----------------|----------|

### Bolt and Screw Sizes

|                                        |     |
|----------------------------------------|-----|
| Number of Wire Binding Screws per Port | 1   |
| Wire Binding Screw Size                | NA  |
| Wire Binding Torque                    | 500 |

### General

|              |   |
|--------------|---|
| Bag Quantity | 1 |
|--------------|---|

|                             |                 |
|-----------------------------|-----------------|
| Carton Quantity Description | STD PACK QTY 20 |
| Direct Burial               | No              |
| Dual Rated                  | Yes             |
| NEMA Code                   | S-588-4         |
| UPC Code                    | 78366900835     |

### Testing Standards

|                          |                                                                                                                     |
|--------------------------|---------------------------------------------------------------------------------------------------------------------|
| CSA File Number          | 72632                                                                                                               |
| CSA Standard             | C22.2 No. 65                                                                                                        |
| Prop65 Compliance        | This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation |
| UL Control Number        | 670B                                                                                                                |
| UL / CULUS Specification | UL 486A/B Listed                                                                                                    |
| UL File Number           | E6207                                                                                                               |

### Environment and Temperature

|                    |      |
|--------------------|------|
| Temperature Rating | 90°C |
|--------------------|------|

### Color

|       |        |
|-------|--------|
| Color | Silver |
|-------|--------|

### Conductor Ranges

|                                                        |                         |
|--------------------------------------------------------|-------------------------|
| Conductor Range AL Solid (Secondary, tap, load)        | NA                      |
| Conductor Range AL Stranded (Primary, run, main, line) | 4/0 Str - 2 Str COMPACT |
| Conductor Range AL Stranded (Secondary, tap, load)     | 4/0 Str - 6 Str         |
| Conductor Range CU Solid (Primary, run, main, line)    | NA                      |
| Conductor Range CU Solid (Secondary, tap, load)        | NA                      |
| Conductor Range CU Stranded (Primary, run, main, line) | 4/0 Str - 2 Str COMPACT |
| Conductor Range CU Stranded (Secondary, tap, load)     | 4/0 Str - 6 Str         |
| Conductor Range AL Solid (Primary, run, main, line)    | NA                      |

### Voltage

|                |       |
|----------------|-------|
| Voltage Rating | 35 kV |
|----------------|-------|