



**SKU:** BGC-2DB

**UPC:** 0783669009910

**Features & Benefits:**

**Description:** Permagraund Brass Ground Clamp, Conductor Range 2-10, Pipe Sizes 1-1/4 to 2in, UL, Direct Bury

## Specs

### Additional Class Attributes

Connection	Mechanical
Number of Conductors	1
Wire Orientation	Parallel

### Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	10 Sol
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	2 Str - 10 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA
NPS/IPS Pipe Size	2

### Dimensions

Drive Size Main	NA
Height (IN)	0
Height BX (IN)	3.75
Length (IN)	0
Weight (LB)	0.4981
Weight BX (LB)	5.1761
Width (IN)	0
Width BX (IN)	6

### Material and Finish

Conductor Material	Copper
Connector Finish	NA
Insulation	NA
Material	Silicon bronze

### Additional Technical Specifications

Conductor Type	Solid
----------------	-------

### **Bolt and Screw Sizes**

<b>Number of Wire Binding Screws per Port</b>	1
<b>Wire Binding Screw Size</b>	NA

### **General**

<b>Bag Quantity</b>	1
<b>Carton Quantity Description</b>	STD PACK QTY 10
<b>Direct Burial</b>	Yes
<b>Dual Rated</b>	No
<b>NEMA Code</b>	S-573-2
<b>UPC Code</b>	78366900991

### **Testing Standards**

<b>CSA File Number</b>	LR-701570
<b>CSA Standard</b>	C22.2 No. 41
<b>Prop65 Compliance</b>	WARNING: Cancer and Reproductive Harm - <a href="http://www.P65warnings.ca.gov">www.P65warnings.ca.gov</a>
<b>UL Control Number</b>	8M24
<b>UL / CULUS Specification</b>	UL 467 Listed
<b>UL File Number</b>	E158587