



**SKU:** CTL-2

**UPC:** 0783669127751

**Features & Benefits:**

**Description:** Surecrimp Copper Compression Sleeve, Conductor Size 2, Long Barrel, Tin Plated, UL, CSA

## Specs

### Additional Class Attributes

|                           |             |
|---------------------------|-------------|
| Barrel Marking            | Ink         |
| Barrel Type               | Long        |
| Connecting Angle          | 180°        |
| Connection                | Compression |
| Contains DE-OX®           | No          |
| Flared End                | No          |
| ILSCOs Die Catalog Number | ILD-33      |
| ILSCOs Die Index Number   | I-33        |
| Number of Conductors      | 1           |
| Sight Window              | No          |
| Slotted                   | No          |

### Dimensions

|                       |         |
|-----------------------|---------|
| Height (IN)           | 0.422   |
| Height BX (IN)        | 2.25    |
| Height (mm)           | 10.7188 |
| Inside Diameter (IN)  | 0.312   |
| Inside Diameter (mm)  | 7.9248  |
| Length (IN)           | 2.625   |
| Length (mm)           | 66.675  |
| Outside Diameter (IN) | 0.422   |
| Outside Diameter (mm) | 10.7188 |
| Weight (LB)           | 0.064   |
| Weight BX (LB)        | 2.5     |
| Width (IN)            | 0.422   |
| Width BX (IN)         | 5       |
| Width (mm)            | 10.7188 |

### Conductor Ranges

|                                                        |               |
|--------------------------------------------------------|---------------|
| Conductor Range AL Stranded (Primary, run, main, line) | NA            |
| Conductor Range CU Solid (Primary, run, main, line)    | 2 Sol         |
| Conductor Range CU Stranded (Primary, run, main, line) | 2 Str         |
| Conductor Range AL Solid (Primary, run, main, line)    | NA            |
| Expanded Conductor Range                               | 2 Str - 6 Str |
| Flex Conductor Range                                   | NA            |

## Material and Finish

|                    |        |
|--------------------|--------|
| Conductor Material | Copper |
| Connector Finish   | Tin    |
| Insulation         | NA     |
| Material           | Copper |

## Additional Technical Specifications

|                |          |
|----------------|----------|
| Conductor Type | Stranded |
|----------------|----------|

## General

|                             |                 |
|-----------------------------|-----------------|
| Bag Quantity                | 1               |
| Carton Quantity Description | STD PACK QTY 25 |
| Direct Burial               | Yes             |
| Dual Rated                  | No              |
| NEMA Code                   | S-588-1         |
| UPC Code                    | 78366912775     |

## Bolt and Screw Sizes

|                         |    |
|-------------------------|----|
| Mounting Bolt/Stud Size | NA |
|-------------------------|----|

## Testing Standards

|                          |                                                                                                                     |
|--------------------------|---------------------------------------------------------------------------------------------------------------------|
| CSA File Number          | LR-29601                                                                                                            |
| CSA Standard             | C22.2 No. 65-03                                                                                                     |
| NEBS Rating              | Level 3                                                                                                             |
| Prop65 Compliance        | This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation |
| UL Control Number        | 453G                                                                                                                |
| UL / CULUS Specification | UL 467 Listed                                                                                                       |
| UL File Number           | E6207                                                                                                               |

## Environment and Temperature

|                    |      |
|--------------------|------|
| Temperature Rating | 90°C |
|--------------------|------|

## Color

|            |        |
|------------|--------|
| Color      | Silver |
| Color Code | Brown  |

## Voltage

|                |       |
|----------------|-------|
| Voltage Rating | 35 kV |
|----------------|-------|