


SKU: D167-12

UPC: 0783669161724

Features & Benefits:

Description: Copper Neutral Bar, Conductor Range 4-14 Main, 6-14 Tap, 13 Ports



Specs

Additional Class Attributes

Connection	Mechanical
Mounting Hole Type	Thru
Number of Conductors	1
Number of Mounting Holes	2
Number of Poles	1
Number of Ports Tap	12

Dimensions

Dimension G (IN)	1.772
Dimension G (mm)	45.0088
Drive Size Main	NA
Drive Type Main	Slotted
Height (IN)	0.482
Height BX (IN)	2
Height (mm)	12.2428
Length (IN)	5.922
Mounting Bolt/Stud Size (mm)	254
Mounting Hole Diameter (IN)	0.203
Mounting Hole Diameter (mm)	5.1562
Mounting Hole Position (IN)	5 & 10
Mounting Hole Spacing (IN)	1.984
Mounting Hole Spacing (mm)	50.3936
Weight (LB)	0.129609103456461
Weight BX (LB)	4.297
Width (IN)	0.342
Width BX (IN)	6.1875
Width (mm)	8.6868

Material and Finish

Conductor Material	Copper
Connector Finish	NA
Insulation	NA
Material	Copper
Wire Binding Hardware Finish	Zinc Clear Trivalent Chromate
Wire Binding Hardware Material	Steel

Additional Technical Specifications

Conductor Type	Solid
----------------	-------

Bolt and Screw Sizes

Mounting Bolt/Stud Size	#10
Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	1/4
Wire Binding Torque	10 - 18 AWG = 20

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 20
Dual Rated	No
NEMA Code	0-000-1
UPC Code	78366916172

Testing Standards

CSA File Number	LR-29601
CSA Standard	C22.2 No. 65-03
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
ROHS Indicator	IND
UL Control Number	NA
UL / CULUS Specification	UL 486A/B Recognized
UL File Number	E6207

Color

Color	Copper
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	10 Sol - 14 Sol
Conductor Range CU Solid (Secondary, tap, load)	10 Sol - 14 Sol
Conductor Range CU Stranded (Primary, run, main, line)	4 Str - 14 Str
Conductor Range CU Stranded (Secondary, tap, load)	6 Str - 14 Str
Conductor Range AL Solid (Primary, run, main, line)	NA