



SKU: DBK-2

UPC: 0783669232134

Features & Benefits:

Description: Direct Burial Splice Kit, Dual Rated, Conductor Range 2-8, Includes (1) SPA-2 Splice and (2) Pieces of Heat Shrink, UL, CSA

Specs

Additional Class Attributes

Includes	(1) SPA-2, (2) Pieces of heat shrink
Number of Conductors	2

Dimensions

Height (IN)	1.5
Height BX (IN)	3.75
Height (mm)	38.1
Length (IN)	14
Length (mm)	355.6
Weight (LB)	0.0559682530345732
Weight BX (LB)	3.1613
Width (IN)	4
Width BX (IN)	6.5
Width (mm)	101.6

Material and Finish

Conductor Material	Copper
Material	Aluminum
Wire Binding Hardware Finish	Tin
Wire Binding Hardware Material	Aluminum

Additional Technical Specifications

Conductor Type	Stranded
-----------------------	----------

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 10
Direct Burial	Yes
Dual Rated	Yes
NEMA Code	S-569-1
UPC Code	78366923213

Testing Standards

Prop65 Compliance	WARNING: Cancer and Reproductive Harm - www.P65warnings.ca.gov
UL Control Number	88X4
UL / CULUS Specification	UL 486D Listed
UL File Number	E125087

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Silver
-------	--------

Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	2 Str - 8 Str
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	2 Str - 8 Str
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range AL Solid (Primary, run, main, line)	NA

Voltage

Voltage Rating	600 V
----------------	-------