



**SKU:** IK3-2

**UPC:** 0783669813609

**Features & Benefits:**

**Description:** Three Wire Copper Split Bolt, Conductor Range for Equal Main & Tap 2-6 Sol, UL, CSA

## Specs

### Additional Class Attributes

Connection	Mechanical
Number of Conductors	3
Number of Poles	1

### Conductor Ranges

Conductor Range AL Solid (Secondary, tap, load)	NA
Conductor Range AL Stranded (Primary, run, main, line)	NA
Conductor Range AL Stranded (Secondary, tap, load)	NA
Conductor Range CU Solid (Primary, run, main, line)	NA
Conductor Range CU Solid (Secondary, tap, load)	NA
Conductor Range CU Stranded (Primary, run, main, line)	NA
Conductor Range CU Stranded (Secondary, tap, load)	NA
Conductor Range for Equal Run & Tap Str	2 Str - 5 Str
Conductor Range for Equal Run & Tap Sol	3 Sol - 6 Sol
Conductor Range for Minimum Tap with Maximum Run	14 Str
Conductor Range AL Solid (Primary, run, main, line)	NA
Max Conductor Copperweld - Str	3 No. 7
Max Conductor Copperweld - Type A	3A

### Dimensions

Drive Size Main	13/16
Drive Type Main	External Hex
Height (IN)	0
Height BX (IN)	2.25
Length (IN)	0
Weight (LB)	0.105
Weight BX (LB)	1.109
Width (IN)	0
Width BX (IN)	4.375
Wire Diameter Range Primary (IN)	0.162 - 0.258

### Material and Finish

Conductor Material	Copper
Connector Finish	NA
Insulation	NA

Material	Copper
----------	--------

### Additional Technical Specifications

Conductor Type	Solid
----------------	-------

### Bolt and Screw Sizes

Number of Wire Binding Screws per Port	1
Wire Binding Screw Size	NA

### General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 10
Direct Burial	Yes
Dual Rated	No
NEMA Code	S-588-4
UPC Code	78366981360

### Testing Standards

CSA File Number	LR-701570
CSA Standard	C22.2 No. 65
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	460C
UL / CULUS Specification	UL 467 Listed
UL File Number	E12822

### Environment and Temperature

Temperature Rating	90°C
--------------------	------

### Color

Color	Copper
-------	--------

### Voltage

Voltage Rating	35 kV
----------------	-------