



SKU: TA-350

UPC: 0783669889932

Features & Benefits:

Description: Aluminum Mechanical Lug, Conductor Range 350-6, 1 Port, 1 Hole, 3/8in Bolt Size, Tin Plated, UL, CSA

Specs

Additional Class Attributes

| | |
|----------------------------|------------|
| Connection | Mechanical |
| Contains DE-OX® | No |
| Mounting Hole Type | Thru |
| Number of Conductors | 1 |
| Number of Mounting Holes | 1 |
| Number of Poles | 1 |
| Number of Ports / Wireways | 1 |

Dimensions

| | |
|------------------------------|--------------|
| Dimension G (IN) | 0.5 |
| Drive Size Main | 3/8 |
| Drive Type Main | Internal Hex |
| Height (IN) | 1.25 |
| Height BX (IN) | 3.75 |
| Height (mm) | 31.75 |
| Length (IN) | 2.25 |
| Length (mm) | 57.15 |
| Mounting Bolt/Stud Size (mm) | 965.2 |
| Mounting Hole Diameter (IN) | 0.406 |
| Mounting Hole Diameter (mm) | 10.3124 |
| Mounting Hole Spacing (mm) | 0 |
| Tang Length (IN) | 1.125 |
| Tang Length (mm) | 28.575 |
| Tang Thickness (IN) | 0.25 |
| Tang Thickness (mm) | 6.35 |
| Tang Width (IN) | 1.125 |
| Tang Width (mm) | 28.575 |
| Weight (LB) | 0.163 |
| Weight BX (LB) | 4.285 |
| Width (IN) | 1.125 |
| Width BX (IN) | 6 |
| Width (mm) | 28.575 |

Material and Finish

| | |
|--------------------|--------|
| Conductor Material | Copper |
| Connector Finish | Tin |
| Insulation | NA |

| | |
|--------------------------------|----------|
| Material | Aluminum |
| Wire Binding Hardware Finish | Tin |
| Wire Binding Hardware Material | Aluminum |

Additional Technical Specifications

| | |
|----------------|----------|
| Conductor Type | Stranded |
|----------------|----------|

Bolt and Screw Sizes

| | |
|--|-----|
| Mounting Bolt/Stud Size | 3/8 |
| Number of Wire Binding Screws per Port | 1 |
| Wire Binding Screw Size | 3/4 |
| Wire Binding Torque | 375 |

General

| | |
|-----------------------------|-----------------|
| Bag Quantity | 1 |
| Carton Quantity Description | STD PACK QTY 25 |
| Direct Burial | No |
| Dual Rated | Yes |
| NEMA Code | S-588-3 |
| UPC Code | 78366988993 |

Testing Standards

| | |
|--------------------------|---|
| CSA File Number | LR-29601 |
| CSA Standard | C22.2 No. 65-03 |
| Prop65 Compliance | This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation |
| ROHS Indicator | IND |
| UL Control Number | 453G |
| UL / CULUS Specification | UL 467 Listed |
| UL File Number | E6207 |

Environment and Temperature

| | |
|--------------------|------|
| Temperature Rating | 90°C |
|--------------------|------|

Color

| | |
|-------|--------|
| Color | Silver |
|-------|--------|

Conductor Ranges

| | |
|--|-------------------|
| Conductor Range AL Solid (Secondary, tap, load) | NA |
| Conductor Range AL Stranded (Primary, run, main, line) | 350 kcmil - 6 Str |
| Conductor Range AL Stranded (Secondary, tap, load) | NA |
| Conductor Range CU Solid (Primary, run, main, line) | NA |
| Conductor Range CU Solid (Secondary, tap, load) | NA |
| Conductor Range CU Stranded (Primary, run, main, line) | 350 kcmil - 6 Str |
| Conductor Range CU Stranded (Secondary, tap, load) | NA |
| Conductor Range AL Solid (Primary, run, main, line) | NA |
| Wire Combinations | NA |

Voltage

Voltage Rating

35 kV