



SKU: TLK-3

UPC: 0783669879049

Features & Benefits:

Description: Aluminum Transformer Lug Kit, Dual Rated, Includes (3) TA-250, (22) TA-600, (3) 1/4-20 x 3/4 Bolts, (3) 1/4-20 Nuts, (16) 3/8-16 x 2 Bolts, (16) 3/8-16 Nuts, (16) 3/8 Flat Washer

Specs

Additional Class Attributes

Contains DE-OX®	No
Includes	(3) TA-250, (22) TA-600, (3) 1/4-20 X 3/4 Bolts, (3) 1/4-20 nuts, (16) 3/8-16-(2) Bolts, (16) 3/8-16 nuts, (16) 3/8 flat washer

Dimensions

Height (IN)	4.375
Height BX (IN)	4.25
Height (mm)	111.125
Length (IN)	7.75
Length (mm)	196.85
Weight (LB)	4.89238883798882
Weight BX (LB)	10.1149
Width (IN)	6.75
Width BX (IN)	7.75
Width (mm)	171.45

Material and Finish

Conductor Material	Aluminum
Connector Finish	Tin
Insulation	NA
Material	Aluminum

General

Bag Quantity	1
Carton Quantity Description	STD PACK QTY 1
Direct Burial	No
Dual Rated	Yes
NEMA Code	S-588-3
UPC Code	78366987904

Testing Standards

CSA File Number	LR-29601
-----------------	----------

CSA Standard	C22.2 No. 65-03
Prop65 Compliance	This product is in compliance with Prop65. It is not known to contain any chemicals associated with this regulation
UL Control Number	453G
UL / CULUS Specification	UL 486A/B Listed
UL File Number	E6207

Environment and Temperature

Temperature Rating	90°C
--------------------	------

Color

Color	Silver
-------	--------

Voltage

Transformer kVA Size	100 to 167 (1-PHASE)
Voltage Rating	35 kV