



PL-T Triple 4-Pin Base

PL-T 18W/835/A/4P 1CT/5X10BOX ALTO

Philips Linear Compact Fluorescent Lamps offer designers, specifiers and end-users new levels of efficiencies and versatility in sizes, configurations and application possibilities. With so many elegant fixtures available to complement their small size, high light output and advanced technology, Philips Energy Advantage lamps are fast becoming the preferred choice when maximum efficiency and sleek design solutions are required.

Warnings and Safety

• Lamp contains mercury. Manage in Accord with Disposal Laws. See: www.lamprecycle.org or 1-800-555-0050

Product data

General Information	
Base	GX24Q-2 [GX24q-2]
LSF Preheat 2000 h Rated	99 %
LSF Preheat 4000 h Rated	98 %
LSF Preheat 6000 h Rated	97 %
LSF Preheat 8000 h Rated	90 %

Light Technical	
Color Code	835 [CCT of 3500K]
Initial lumen (Nom)	1175 lm
Luminous Flux (Rated) (Nom)	1175 lm
Color Designation	White (WH)
Correlated Color Temperature (Nom)	3500 K
Luminous Efficacy (rated) (Nom)	65.3 lm/W
Color Rendering Index (Nom)	82
LLMF 2000 h Rated	92 %

Operating and Electrical	
Power (Rated) (Nom)	18.0 W
Lamp Current (Nom)	0.225 A

Temperature	
Design Temperature (Nom)	28 °C

Controls and Dimming	
Dimmable	Yes

LLMF 4000 h Rated	88 %
LLMF 6000 h Rated	85 %
LLMF 8000 h Rated	84 %
LLMF 12000 h Rated	81 %

PL-T Triple 4-Pin Base

Mechanical and Housing

Cap-Base Information 4P


Approval and Application

Mercury (Hg) Content (Nom) 1.4 mg

Product Data

Order product name PL-T 18W/835/A/4P 1CT/5X10BOX ALTO
 EAN/UPC - Product 046677268206
 Order code 458224

Numerator - Quantity Per Pack 1
 Numerator - Packs per outer box 10
 Material Nr. (12NC) 927910583550
 Net Weight (Piece) 58.000 g
 ILCOS Code FSM-18/35/1B-E-GX24q=2



Dimensional drawing


□

Product	D (max)	A (max)	B (max)	C (max)
PL-T 18W/835/A/4P/ALTO	41 mm	71.7 mm	96.0 mm	111.7 mm

PL-T ALTO 18W/835/4P A

Photometric data

ψ 500





LDPB_PLTTOP4P_835-Spectral power distribution B/W

LDPO_PLTTOP4P_835-Spectral power distribution Colour


PL-T Triple 4-Pin Base

Lifetime



LDLM_PLTTOP4P_0001-Lumen maintenance diagram

LDLE_PLTTOP4P_0001-Life expectancy diagram



LDLE_PLTTOP4P_0002-Life expectancy diagram

