



Main

Range	VigiPacT
Device short name	TA30
Product or Component Type	Earth leakage current sensor
Device Application	Equipment monitoring and control
Range compatibility	RH10M residual current protection relay RH10P residual current protection relay RH21M residual current protection relay RH21P residual current protection relay RH68M residual current protection relay RH86M residual current protection relay RH86P residual current protection relay RH99M residual current protection relay RH99P residual current protection relay RH197M residual current protection relay RH197P residual current protection relay RHU residual current protection relay RHUs residual current protection relay RMH residual current protection relay
Current sensor type	A type closed toroid
[Ie] rated operational current	65 A

Complementary

Transformer ratio	1/1000
Network type	AC/DC
Network Frequency	45...440 Hz
[Icw] rated short-time withstand current	85 kA 0.5 s
Residual short-circuit withstand current	85 kA / 0.5 s IEC 60947-2
[Ui] rated insulation voltage	1000 V
Overtoltage category	IV
[Uimp] rated impulse withstand voltage	12 kV
Mounting mode	Fixed plain backplate) Fixed profiled sheet metal) Fixed slotted backplate) Clip-on DIN rail) Clip-on Vigirex relay)
Calorific value	0.98 MJ
Connections - terminals	Screw connection 0.00 in ² (0.22 mm ²)
Diameter	Inner 1.18 in (30 mm)
Cable outer diameter	0.59 in (15 mm) 0.04 in ² (25 mm ²)
Net Weight	0.26 lb(US) (0.12 kg)
Height	3.23 in (82 mm)
Width	2.36 in (60 mm)
Depth	1.14 in (29 mm)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Environment

IP Degree of Protection	Connectors IP20 IP30
Environmental characteristic	Exposure to damp heat not in service 25...55 °C, RH 95 %) 28 cycles IEC 60068-2-30 Salt mist Kb/2 IEC 60068-2-52 Exposure to damp heat in service category C2 48 hours IEC 60068-2-56
Pollution degree	Level 3 IEC 60664-1
Ambient Air Temperature for Operation	-31...158 °F (-35...70 °C)
Ambient Air Temperature for Storage	-67...185 °F (-55...85 °C)
Standards	IEC 60947-2
Product Certifications	CE

Ordering and shipping details

Category	01078-DE2 MISC
Discount Schedule	DE2
GTIN	3303430504375
Nbr. of units in pkg.	1
Package weight(Lbs)	4.16 oz (118.0 g)
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	1.77 in (4.5 cm)
Package 1 width	4.65 in (11.8 cm)
Package 1 Length	7.48 in (19 cm)
Unit Type of Package 2	S04
Number of Units in Package 2	100
Package 2 Weight	27.70 lb(US) (12.566 kg)
Package 2 Height	11.81 in (30 cm)
Package 2 width	15.75 in (40 cm)
Package 2 Length	23.62 in (60 cm)
Unit Type of Package 3	P12
Number of Units in Package 3	400
Package 3 Weight	127.10 lb(US) (57.65 kg)
Package 3 Height	19.69 in (50 cm)
Package 3 width	31.50 in (80 cm)
Package 3 Length	47.24 in (120 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Circularity Profile	End Of Life Information
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

Contractual warranty

Warranty	18 months
----------	-----------
