



### Main

Range	VigiPacT
Device short name	MA120
Product or Component Type	Earth leakage current sensor
Device Application	Equipment monitoring and control
Range compatibility	RH10M residual current protection relay RH10P residual current protection relay RH21M residual current protection relay RH21P residual current protection relay RH68M residual current protection relay RH86M residual current protection relay RH86P residual current protection relay RH99M residual current protection relay RH99P residual current protection relay RH197M residual current protection relay RH197P residual current protection relay RHU residual current protection relay RHUs residual current protection relay RMH residual current protection relay
Current sensor type	A type closed toroid
[Ie] rated operational current	250 A

### Complementary

Transformer ratio	1/1000
Network type	AC/DC
Network Frequency	45...440 Hz
[Icw] rated short-time withstand current	85 kA 0.5 s
Residual short-circuit withstand current	85 kA / 0.5 s IEC 60947-2
[Ui] rated insulation voltage	1000 V
Overvoltage category	IV
[Uimp] rated impulse withstand voltage	12 kV
Mounting mode	Fixed cables) Fixed plain backplate) Fixed profiled sheet metal) Fixed slotted backplate) Clip-on DIN rail)
Calorific value	3.89 MJ
Connections - terminals	Screw connection 0.00 in <sup>2</sup> (0.22 mm <sup>2</sup> )
Diameter	Inner 4.72 in (120 mm)
Cable outer diameter	2.36 in (60 mm) 0.37 in <sup>2</sup> (240 mm <sup>2</sup> )
Net Weight	1.30 lb(US) (0.59 kg)
Height	6.46 in (164 mm)
Width	7.48 in (190 mm)
Depth	1.73 in (44 mm)

## Environment

IP Degree of Protection	Connectors IP20 IP30
Environmental characteristic	Exposure to damp heat not in service 25...55 °C, RH 95 %) 28 cycles IEC 60068-2-30 Salt mist Kb/2 IEC 60068-2-52 Exposure to damp heat in service category C2 48 hours IEC 60068-2-56
Pollution degree	Level 3 IEC 60664-1
Ambient Air Temperature for Operation	-31...158 °F (-35...70 °C)
Ambient Air Temperature for Storage	-67...185 °F (-55...85 °C)
Standards	IEC 60947-2
Product Certifications	CE

## Ordering and shipping details

Category	01078-DE2 MISC
Discount Schedule	DE2
GTIN	3303430504405
Nbr. of units in pkg.	1
Package weight(Lbs)	18.98 oz (538.0 g)
Returnability	Yes
Country of origin	FR

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	2.01 in (5.1 cm)
Package 1 width	6.93 in (17.6 cm)
Package 1 Length	7.95 in (20.2 cm)
Unit Type of Package 2	P12
Number of Units in Package 2	104
Package 2 Weight	154.96 lb(US) (70.288 kg)
Package 2 Height	19.69 in (50 cm)
Package 2 width	31.50 in (80 cm)
Package 2 Length	47.24 in (120 cm)
Unit Type of Package 3	S04
Number of Units in Package 3	26
Package 3 Weight	31.61 lb(US) (14.34 kg)
Package 3 Height	11.81 in (30 cm)
Package 3 width	15.75 in (40 cm)
Package 3 Length	23.62 in (60 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: DINP, which is known to the State of California to cause cancer, and DIDP, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

---

Circularity Profile	<a href="#">End Of Life Information</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

---

**Contractual warranty**

Warranty	18 months
----------	-----------

---