



### Main

Range	Linergy
Product name	FT
Device short name	GV2G
Product or Component Type	Comb busbar
Accessory / separate part category	Connection accessory
Poles description	3P
Range compatibility	TeSys D TeSys GV2 TeSys K TeSys U
Number of tap-offs	3
[I <sub>th</sub> ] conventional free air thermal current	63 A
Connection pitch	2.13 in (54 mm)

### Complementary

Mounting Location	On terminal
[U <sub>i</sub> ] rated insulation voltage	690 V
Length	5.98 in (152 mm)
Net Weight	0.13 lb(US) (0.06 kg)

### Ordering and shipping details

Category	22367-MANUAL STR PROTECTOR - GV2
Discount Schedule	I11
GTIN	3389110555912
Nbr. of units in pkg.	1
Package weight(Lbs)	2.26 oz (64.0 g)
Returnability	Yes
Country of origin	RO

### Packing Units

Unit Type of Package 1	PCE
Package 1 Height	0.39 in (1 cm)
Package 1 width	1.22 in (3.1 cm)
Package 1 Length	5.94 in (15.1 cm)
Unit Type of Package 2	P06
Number of Units in Package 2	2240
Package 2 Weight	350.67 lb(US) (159.06 kg)
Package 2 Height	30.31 in (77 cm)
Package 2 width	31.50 in (80 cm)
Package 2 Length	23.62 in (60 cm)
Unit Type of Package 3	S01
Number of Units in Package 3	70
Package 3 Weight	10.12 lb(US) (4.589 kg)
Package 3 Height	5.91 in (15 cm)

Package 3 width	5.91 in (15 cm)
Package 3 Length	15.75 in (40 cm)

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>


### Contractual warranty

Warranty	18 months
----------	-----------

---

Sets of Busbars GV2G345 and GV2G354

---



	l
GV2G345 (3 x 45 mm)	134
GV2G354 (3 x 54 mm)	152