



### Main

|                                    |   |
|------------------------------------|---|
| Range                              | TeSys   |
| Product or Component Type          | Electrical remote tripping  |
| Device short name                  | LA7D  |
| Accessory / separate part category | Electrical accessory  |
| Product Compatibility              | LRD43..<br>LR3D15..<br>LR2D<br>LRD33..<br>LR3D43..<br>LR3D35..<br>LRD15..<br>LR3D33.. |
| [Uc] control circuit voltage       | 110 V AC 50/60 Hz<br>110 V DC   |

### Complementary

|                            |                       |
|----------------------------|-----------------------|
| Maximum inrush power in VA | 100 VA                |
| Inrush power in W          | 0...100 W             |
| Net Weight                 | 0.20 lb(US) (0.09 kg) |

### Ordering and shipping details

|                       |                               |
|-----------------------|-------------------------------|
| Category              | 22341-CONTACTOR,D,K,&F ACCESS |
| Discount Schedule     | I12                           |
| GTIN                  | 3389110055122                 |
| Nbr. of units in pkg. | 1                             |
| Package weight(Lbs)   | 3.81 oz (108.0 g)             |
| Returnability         | Yes                           |
| Country of origin     | FR                            |

### Packing Units

|                              |                        |
|------------------------------|------------------------|
| Unit Type of Package 1       | PCE                    |
| Package 1 Height             | 1.89 in (4.8 cm)       |
| Package 1 width              | 1.89 in (4.8 cm)       |
| Package 1 Length             | 1.97 in (5 cm)         |
| Unit Type of Package 2       | S01                    |
| Number of Units in Package 2 | 32                     |
| Package 2 Weight             | 7.95 lb(US) (3.608 kg) |
| Package 2 Height             | 5.91 in (15 cm)        |
| Package 2 width              | 5.91 in (15 cm)        |
| Package 2 Length             | 15.75 in (40 cm)       |

The information provided in this documentation contains general descriptions and/or technical characteristics of the products of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Offer Sustainability

|                            |  |
|----------------------------|--|
| Sustainable offer status   | Green Premium product  |
| REACH Regulation           | <a href="#">REACH Declaration</a>  |
| REACH free of SVHC         | Yes  |
| EU RoHS Directive          | Compliant <a href="#">EU RoHS Declaration</a>  |
| Toxic heavy metal free     | Yes  |
| Mercury free               | Yes  |
| RoHS exemption information | <a href="#">Yes</a>  |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>   |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>  |
| Circularity Profile        | <a href="#">End Of Life Information</a>  |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins. |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|