

# LS1D30

Fuse Holder, TeSys LS1, 3P, 30A, fuse type CC or KTKR, 0.41in x 1.5in fuse, DIN rail mount, screw type terminals



## Main

Range	TeSys
Product name	TeSys LS1
Product or Component Type	Fuse-disconnector
Device short name	LS1D
Poles description	3P

## Complementary

Mounting Support	Rail
Mounting position	Vertical +/- 23°)
Control Type	Toggle
[Ue] rated operational voltage	600 V
[Ie] rated operational current	30 A power circuit
Local signalling	Blown fuse indication
Fuse size	0.41 x 1.50 in
Fuse type	CC
Connections - terminals	Screw clamp terminals 2 0.00...0.01 in <sup>2</sup> (1...6 mm <sup>2</sup> )solid Screw clamp terminals 2 0.00...0.01 in <sup>2</sup> (1...6 mm <sup>2</sup> )flexible without cable end Screw clamp terminals 2 0.00...0.01 in <sup>2</sup> (1...4 mm <sup>2</sup> )flexible with cable end
Tightening torque	15.05 lbf.in (1.7 N.m) screw clamp terminals

## Environment

Standards	IEC 60947-1 IEC 60947-2 IEC 60947-4-1 UL 508
Product Certifications	UL CSA
IP degree of protection	IP20
Protective treatment	TH
Ambient air temperature for operation	-58...158 °F (-50...70 °C) operation
Height	3.50 in (89 mm)
Width	1.77 in (45 mm)
Depth	2.69 in (68.3 mm)
Net Weight	0.66 lb(US) (0.3 kg)

## Ordering and shipping details

Category	22341-CONTACTOR,D,K,&F ACCESS
Discount Schedule	I12
GTIN	3389110273083
Nbr. of units in pkg.	1
Package weight(Lbs)	6.63 oz (188.0 g)

Returnability	No
Country of origin	MX

### Packing Units

Unit Type of Package 1	PCE
Package 1 Height	2.05 in (5.2 cm)
Package 1 width	3.03 in (7.7 cm)
Package 1 Length	4.33 in (11 cm)

### Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.

### Contractual warranty

Warranty	18 months
----------	-----------