

# NSYPTDS4

## Spacial - Flush Mounting drive installation kit - Altivar Process size S4 - IP55



### Main

|  |   |
|--|---|
| Range  | Spacial   |
| Product or Component Type                        | Drive flush mounting kit  |
| Accessory category                               | Mounting and fixing accessory   |
| Product Specific Application                     | Process and utilities   |
| Range compatibility                              | Altivar variable speed drive ATV630<br>Altivar variable speed drive ATV930<br>Spacial SF and SM enclosures<br>Altivar variable speed drive ATV340   |
| Compatibility for Altivar Process 630-930, size: | 4   |
| Motor power kW                                   | 15 KW 220/240 V<br>18.5 KW 220/240 V<br>22 KW 220/240 V<br>30 KW 380/480 V<br>37 KW 380/480 V<br>45 kW 380/480 V  |
| Mounting location                                | 1 back of enclosure mounting plate<br>2 inside enclosure  |
| Kit composition                                  | 1 x mounting plate with flanges and integrated gasket, steel with anti-corrosive coating by screws and nuts<br>1 x fixing accessories<br>1 x drilling template<br>1 x instruction sheet<br>1 x edge protector profile, plastic<br>1 x fan support<br>1 x cover for fan protection |

### Complementary

|                            |  |
|----------------------------|--|
| Permanent permissible load | 63.27 lb(US) (28.7 kg)   |
| Color                      | Gray RAL 7035)   |
| Height                     | External 31.50 in (800 mm)<br>Cut-out 28.94 in (735 mm)                                      |
| Width                      | External 15.16 in (385 mm)<br>Cut-out 12.80 in (325 mm)                                      |
| Depth                      | Wall-enclosure separation 5.96 in (151.5 mm)   |
| Net Weight                 | 17.86 lb(US) (8.102 kg)  |
| Services                   | Configuration of enclosure pre-drilled back<br>Factory installation drive flush mounting kit |

### Environment

|                         |                              |
|-------------------------|------------------------------|
| IP degree of protection | IP55 conforming to IEC 60529 |
|-------------------------|------------------------------|

### Ordering and shipping details

|                       |                           |
|-----------------------|---------------------------|
| Category              | 22277-ATV930 FRAMES 3 & 4 |
| Discount Schedule     | CP4E                      |
| GTIN                  | 3606485442471             |
| Nbr. of units in pkg. | 1                         |
| Package weight(Lbs)   | 11.02 lb(US) (5.0 kg)     |
| Returnability         | Yes                       |
| Country of origin     | FR                        |

## Packing Units

|                              |                         |
|------------------------------|-------------------------|
| Unit Type of Package 1       | PCE                     |
| Package 1 Height             | 4.72 in (12 cm)         |
| Package 1 width              | 7.87 in (20 cm)         |
| Package 1 Length             | 33.07 in (84 cm)        |
| Unit Type of Package 2       | P12                     |
| Number of Units in Package 2 | 10                      |
| Package 2 Weight             | 137.79 lb(US) (62.5 kg) |
| Package 2 Height             | 29.53 in (75 cm)        |
| Package 2 width              | 31.50 in (80 cm)        |
| Package 2 Length             | 47.24 in (120 cm)       |

## Offer Sustainability

|                            |  |
|----------------------------|--|
| REACH Regulation           | <a href="#">REACH Declaration</a>  |
| REACH free of SVHC         | Yes  |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a> |
| Mercury free               | Yes  |
| RoHS exemption information | <a href="#">Yes</a>  |
| China RoHS Regulation      | <a href="#">China RoHS Declaration</a>   |