



Main

Range of Product	PowerPact L
Product or Component Type	Mechanical lug
Accessory / separate part category	Connection accessory
Quantity per Set	Set of 3
Circuit breaker type	L-Frame

Complementary

Product compatibility	PowerPact L PowerPact L-Frame
Line Rated Current	400 A
Material	Aluminium
Mounting Mode	Unit mount Compression
AWG gauge	500 kcmil copper 500...750 kcmil aluminium
Tightening torque	247.82 Lbf.in (28 N.m) 0.37...0.62 in ² (240...400 mm ²) (500...750 kcmil) 442.54 lbf.in (50 N.m) 0.37 in ² (240 mm ²) (500 kcmil)

Environment

Product certifications	CSA UL
------------------------	-----------

Ordering and shipping details

Category	01103-H,J,COMPACT NS UL/IEC CIRCUIT BREAKER ACCESSORIES
Discount Schedule	DE2
GTIN	785901309819
Nbr. of units in pkg.	1
Package weight(Lbs)	28.80 oz (816.466 g)
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	5.88 in (14.923 cm)
Package 1 width	5.25 in (13.335 cm)
Package 1 Length	10.75 in (27.305 cm)

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile
Circularity Profile	End Of Life Information
PVC free	Yes

Contractual warranty

Warranty	18 months
----------	-----------