



Main

Product or Component Type	Coil
Accessory / separate part destination	Class 8502 type SG contactor Class 8903 type SY/SX lighting contactor Class 8910 type SYD368 (series A) contactor

Complementary

NEMA size	5
[Ue] rated operational voltage	120 V AC 60 Hz 110 V AC 50 Hz
Inrush power in VA	2970 VA
Average consumption	212 VA 250 VA
Height	5.53 in (140.5 mm)
Width	3.98 in (101.2 mm)
Depth	1.78 in (45.3 mm)

Ordering and shipping details

Category	18079-SPARE PARTS DISCOUNT CP10
Discount Schedule	CP10
GTIN	785901326892
Nbr. of units in pkg.	1
Package weight(Lbs)	2.63 lb(US) (1.193 kg)
Returnability	Yes
Country of origin	MX

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	4.10 in (10.414 cm)
Package 1 width	5.70 in (14.478 cm)
Package 1 Length	6.20 in (15.748 cm)
Unit Type of Package 2	PAL
Number of Units in Package 2	25
Package 2 Weight	66.00 lb(US) (29.937 kg)
Package 2 Height	40.00 in (101.6 cm)
Package 2 width	40.00 in (101.6 cm)
Package 2 Length	48.00 in (121.92 cm)

Offer Sustainability

EU RoHS Directive	Not applicable, out of EU RoHS legal scope
-------------------	--

Contractual warranty

Warranty	18 months
----------	-----------
