



Main

Range of Product	9007
Series name	Heavy duty
Device short name	C
Head type	Turret head rotary lever
Type of operator	Spring return lever arm first stage : 10° - second stage : 2.5°) to be ordered separately Spring return lever arm standard pre-travel)
Switch actuation	CCW
Cable entry	NPT conduit entry 0.5 in (12.7 mm)
Contacts type and composition	2 NO/2 NC
Contact operation	Snap action Two stage

Complementary

Body Material	Zinc alloy
Switch Function	SPDT-DB
Contact form	Form ZZ
Contacts material	Silver alloy (Ag/Ni)
Minimum torque for tripping	4 lbf.in (0.5 N.m)
Tripping angle	4 °
Maximum displacement angle	90 °
[Ie] rated operational current	10 A, A600 10 A, R300
[Ui] rated insulation voltage	600 V
Product Certifications	CSA[RETURN]CE[RETURN]UL Listed
Provided equipment	Receptacle

Environment

Ambient air temperature for operation	-29...85 °C (-20...185 °F)
---------------------------------------	----------------------------



Ordering and shipping details

Category	US10DS121499
Discount Schedule	0DS1
GTIN	785901046165
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.69 in (4.3 cm)
Package 1 Width	2.80 in (7.1 cm)
Package 1 Length	4.21 in (10.7 cm)
Package 1 Weight	20.3 oz (576.1 g)

Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
RoHS exemption information	 Yes
Environmental Disclosure	 Product Environmental Profile
Circularity Profile	No need of specific recycling operations

Contractual warranty

Warranty	18 months
----------	-----------