

## Main

Range of Product	9007
Series name	Heavy duty
Product or Component Type	Limit switch lever
Device short name	9007C
Associated head	9007A 9007C 9007T10 9007T5 9007B 9007N
Associated complete product	9007C 9007AW
Movement of operating head	Rotary
Type of operator	Cast zinc spring return adjustable roller lever 0.88... 4 in (22.35...101.6 mm) - -
Type of roller	1 steel outside roller 0.63 in (16.002 mm) 0.25 in (6.35 mm)
Type of approach	Lateral approach
Positive opening	Without

## Complementary

Switch actuation	By 30° cam
Net Weight	0.1 lb(US) (0.05 kg)

## Environment

Ambient Air Temperature for Operation	-29...85 °C (-20...185 °F)
Ambient Air Temperature for Storage	-29...85 °C (-20...185 °F)
Environmental characteristic	Standard environment

## Ordering and shipping details



Category	US1000T22413
Discount Schedule	000T
GTIN	785901743729
Returnability	Yes
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	0.60 in (1.524 cm)
Package 1 Width	0.80 in (2.032 cm)
Package 1 Length	4.70 in (11.938 cm)
Package 1 Weight	1.600 oz (45.359 g)
Unit Type of Package 2	S01
Number of Units in Package 2	25
Package 2 Height	5.91 in (15.0 cm)

Package 2 Width	5.91 in (15.0 cm)
Package 2 Length	15.75 in (40.0 cm)
Package 2 Weight	3.532 lb(US) (1.602 kg)

### Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope)
Mercury free	Yes
RoHS exemption information	 Yes
Environmental Disclosure	 <a href="#">Product Environmental Profile</a>
Circularity Profile	No need of specific recycling operations

### Contractual warranty

Warranty	18 months
----------	-----------