

Product data sheet

Characteristics

9070SK3000A2D1

Transformer disconnect, 3000VA, 240x480VAC primary, 120VAC secondary, without outlet, Type 12

Main

Product	Transformer Disconnect
Certifications	UL Listed CSA
Enclosure Type	NEMA 12 standard
Insulation Temperature	356 °F (180 °C)
Phase	1 phase
Primary Voltage	240 x 480 V
Power Rating	3000 VA
Secondary Voltage	120 V
Temperature Rise	115 °C
Electrical Connection	Screw clamp terminals
Type	SK

Ordering and shipping details

Category	21694-9070 SK
Discount Schedule	CP8
GTIN	785901058687
Number of Units in Package 1	1
Package 1 Weight	99.00 lb(US) (44.906 kg)
Returnability	No
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	16.00 in (40.64 cm)
Package 1 Width	18.00 in (45.72 cm)
Package 1 Length	24.00 in (60.96 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Phenyl Glycidyl Ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration

Contractual warranty

Warranty	18 months
----------	-----------