



Main

| | |
|---------------------------|---|
| Product or Component Type | Industrial Control Transformer |
| Power Rating | 500 VA |
| Primary Voltage | 230 x 460 V 220 x 440 V 240 x 480 V |
| Secondary Voltage | 110/220 V 120/240 V 115/230 V |
| Type | TF |

Complementary

| | |
|--------------------------------|---|
| Number of Phases | 1 phase |
| Power Rating | 500 VA UL 500 VA CSA 500 VA NOM 300 VA |
| Primary to Secondary Voltage | 220 x 440 V 110/220 V 230 x 460 V 115/230 V 240 x 480 V 120/240 V |
| Fuse type | 0.41 x 1.50 in CC top |
| Temperature rise | 115 °C |
| Electrical Connection | Screw clamp terminals |
| Height | 5.13 in (130.30 mm) |
| Width | 4.5 in (114.30 mm) |
| Depth | 5.49 in (139.45 mm) |
| Material | Copper winding |
| Fingersafe Cover Compatibility | FSC2 |

Environment

| | |
|------------------------|--|
| Product certifications | CSA file LR37055 guide 184-N-90 UL listed file E61239 |
| Enclosure Type | Not rated (open device) |
| Insulation temperature | 356 °F (180 °C) |

Ordering and shipping details

| | |
|-----------------------|---------------------------|
| Category | 16207-9070 TF (NOT T) MTO |
| Discount Schedule | CP8 |
| GTIN | 785901928263 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 11.90 lb(US) (5.398 kg) |
| Returnability | No |
| Country of origin | US |

Packing Units

| | |
|------------------------|--------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 6.00 in (15.24 cm) |
| Package 1 width | 7.50 in (19.05 cm) |
| Package 1 Length | 6.50 in (16.51 cm) |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Phenyl glycidyl ether, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| PVC free | Yes |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|