

# D325NR

Safety switch, general duty, fusible, 400A, 3 poles, 125hp, 240VAC, NEMA 3R, neutral factory installed



## Main

Product	Single Throw Safety Switch
Duty Rating	General duty
Device application	Residential
Disconnect Type	Fusible disconnect switch
Factory Installed Neutral	Neutral (factory installed)
Phase	3 phase
Number of Poles	3
Current Rating	400 A
Voltage Rating	240 V AC
Enclosure Rating NEMA	NEMA 3R
Maximum Horse Power Rating	50 Hp 240 V at AC 60 Hz for 3 phase conforming to NEC 240.6 125 hp 240 V at AC 60 Hz for 3 phase conforming to NEC 430.52

## Complementary

Short Circuit Current Rating	100 kA maximum depending on fuse H, K, J or R
Fuse type	H, K, J or R
Mounting Type	Surface
Electrical Connection	Lugs
Wiring configuration	4-wire (3PH + G)
Wire Size	AWG 10...AWG 6 aluminium/copper
Tightening torque	340 lbf.in (38.41 N.m) (AWG 1/0...250 kcmil)
Depth	10.13 in (257.30 mm)
Width	22.25 in (565.15 mm)
Height	30.63 in (778.00 mm)
Net weight	99.21 lb(US) (45 kg)

## Environment

Certifications	UL listed file E2875
----------------	----------------------

## Ordering and shipping details

Category	00107 - D & DU SW,NEMA3R, 400-600A
Discount Schedule	DE1A
GTIN	785901461579
Nbr. of units in pkg.	1
Package weight(Lbs)	69.98 lb(US) (31.742 kg)
Returnability	Yes
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	11.00 in (27.94 cm)
Package 1 width	23.00 in (58.42 cm)
Package 1 Length	32.00 in (81.28 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
PVC free	Yes
Halogen content performance	Halogen free plastic parts product

## Contractual warranty

Warranty	18 months
----------	-----------