

H361DF

Safety switch, heavy duty, fusible, 30A, 3 poles, 20hp, 20hp, 600VAC/DC, NEMA 4X, fiberglass reinforced polyester



Main

| | |
|----------------------------|---|
| Product | Single Throw Safety Switch |
| Duty Rating | Heavy duty |
| Device application | Heavy application |
| Disconnect Type | Fusible disconnect |
| Factory Installed Neutral | None |
| Phase | 3 phase |
| Number of Poles | 3 |
| Current Rating | 30 A |
| Voltage Rating | 600 V AC/DC |
| Enclosure Rating | NEMA 4X fiberglass reinforced polyester |
| Maximum Horse Power Rating | 5 Hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 15 Hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 7.5 Hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 240.6 20 Hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 15 hp 600 V at DC |

Complementary

| | |
|------------------------------|---|
| Short Circuit Current Rating | 10 KA H or K 200 kA R or J |
| Fuse type | H or K R or J |
| Mounting Type | Surface |
| Electrical Connection | Lugs |
| Wiring configuration | 3-wire (3P) |
| Wire Size | AWG 12...AWG 6 aluminium AWG 14...AWG 6 copper |
| Tightening torque | 45 Lbf.In (5.08 N.m) 0.02 in ² (13.3 mm ²) (AWG 6) 40 Lbf.In (4.52 N.m) 0.01 in ² (8.367 mm ²) (AWG 8) 35 lbf.in (3.95 N.m) 0.00...0.01 in ² (2.06...5.261 mm ²) (AWG 14...AWG 10) |
| Depth | 8.8 in (223.52 mm) |
| Width | 11 in (279.40 mm) |
| Height | 16.5 in (419.10 mm) |
| Net Weight | 22.05 lb(US) (10 kg) |

Environment

| | |
|----------------|----------------------|
| Certifications | UL listed file E2875 |
|----------------|----------------------|

Ordering and shipping details

| | |
|-----------------------|---------------------------------|
| Category | 00111-H&HU SW,N4X(DF,DX)NON-MET |
| Discount Schedule | DE1 |
| GTIN | 785901627845 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 20.96 lb(US) (9.507 kg) |
| Returnability | Yes |
| Country of origin | US |

Packing Units

| | |
|------------------------|----------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 11.20 in (28.448 cm) |
| Package 1 width | 12.50 in (31.75 cm) |
| Package 1 Length | 19.80 in (50.292 cm) |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| PVC free | Yes |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|