



Main

| | |
|----------------------------|---|
| Product | Double Throw Safety Switch |
| Duty Rating | General duty |
| Disconnect Type | Non-fusible disconnect |
| Factory Installed Neutral | None |
| Number of Poles | 3 |
| Current Rating | 200 A |
| Voltage Rating | 480 V AC 250 V DC |
| Enclosure Rating | NEMA 1 |
| Maximum Horse Power Rating | 15 hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 |

Complementary

| | |
|-----------------------|--|
| Short-circuit current | 10 kA H or J |
| Fuse type | H or J |
| Mounting Type | Surface |
| Wire Size | AWG 6...300 kcmil copper or aluminium |
| Tightening torque | 340 lbf.in (38.41 N.m) (AWG 6...300 kcmil) |
| Depth | 10.63 in (270.00 mm) |
| Width | 26.25 in (666.75 mm) |
| Height | 32.5 in (825.50 mm) |
| Net Weight | 136.69 lb(US) (62 kg) |




Environment

| | |
|----------------|-----------|
| Certifications | UL Listed |
|----------------|-----------|

Ordering and shipping details

| | |
|-----------------------|------------------------|
| Category | 00134-DT SWITCH,NEMA12 |
| Discount Schedule | DE1 |
| GTIN | 785901077077 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 143 lb(US) (64.86 kg) |
| Returnability | No |
| Country of origin | US |

Offer Sustainability

| | |
|----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| RECh Regulation |  RECh Declaration |
| RECh free of SVHC | Yes |
| EU RoHS Directive | Compliant  EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information |  Yes |

| | |
|-----------------------------|---|
| China RoHS Regulation | China RoHS Declaration |
| Environmental Disclosure | Product Environmental Profile |
| PVC free | Yes |
| Halogen content performance | Halogen free plastic parts product |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|