

# Product data sheet

## Characteristics

# HOM2175SB

Surge protection device, Surgebreaker, 22.5kA, 120/240VAC, 1 phase, 3 wire, SPD type 2



### Main

Product	Surge protection device
Range	Homeline

### Complementary

Surge Current	22.5 kA
Voltage Rating	120/240 V AC
Number of Phases	1 phase
Wiring Configuration	3-wire
MCOV	150 V 300 V
Rated Current	5 kA
SCCR	22 kA
Local Signalling	1 LED green normal operation
Product destination	Load center Homeline
Height	3.7 in (93.98 mm)
Width	2 in (50.80 mm)
Depth	2.6 in (66.04 mm)

### Environment

Enclosure Rating	NEMA 1
Standards	UL 1449:ed. 4: type II
Ambient Operating	149 °F (65 °C)

### Ordering and shipping details

Category	08461-SURGE PROTECTION RESI
Discount Schedule	DE1B
GTIN	785901210900
Returnability	Yes
Country of origin	MX

### Packing Units

Unit Type of Package 1	PCE
Package 1 Length	5.30 in (13.462 cm)
Number of Units in Package 1	1
Package 2 Width	6.10 in (15.494 cm)
Package 2 Height	7.00 in (17.78 cm)
Package 2 Weight	16.56 lb(US) (7.511 kg)
Package 1 Width	2.70 in (6.858 cm)

Package 1 Height	2.20 in (5.588 cm)
Package 1 Weight	12.96 oz (367.41 g)
Number of Units in Package 2	20
Unit Type of Package 2	CAR
Package 2 Length	21.30 in (54.102 cm)

### Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
EU RoHS Directive	Under investigation

### Contractual warranty

Warranty	18 months
----------	-----------