






NEMA TYPE 3R
NO KNOCKOUTS

NOTES:
FINISH - GRAY BAKED ENAMEL
UL LISTED - FILE E-154828
ALL NEUTRALS - INSULATED GROUNDABLE
SUITABLE FOR USE AS SERVICE EQUIPMENT
SHORT CIRCUIT CURRENT RATINGS:
10,000 AMPERES WHEN USED WITH OR PROTECTED BY CLASS H OR K FUSES.
200,000 AMPERES WHEN USED WITH OR PROTECTED BY CLASS R FUSES HAVING
CLASS R REJECTION KITS INSTALLED OR CLASS J FUSES.
*FOR CORNER GROUNDED DELTA SYSTEMS ONLY AND WITH SOLID NEUTRAL ASSEMBLY INSTALLED.
■ NEUTRAL ASSEMBLY H600SN MUST BE USED FOR 480VAC, CORNER GROUNDED DELTA SYSTEM.



NOTE: SIDE HINGED DOOR



TERMINAL LUGS DATA				
AMPERES	MAX WIRE	MIN WIRE	TYPE	
400	(1) 750 KCML OR	(1) #1/0 AWG OR	AL OR CU	
	(2) 300 KCML	(2) #1/0 AWG		

DUAL DIMENSIONS: INCHES MILLIMETERS							
CATALOG NUMBER	VOLTAGE RATINGS	WIRING DIAG	HORSEPOWER RATINGS				
			240VAC		480VAC		250 VDC
			STD	MAX	STD	MAX	MAX
H225NR	240VAC;250VDC	B	50*	125*	—	—	—
H225R	240VAC;250VDC	A	—	—	—	—	50
H265R	600VAC;600VDC	A	—	—	100■	250■	50
HU265R	600VAC;600VDC	C	—	—	—	—	50

HEAVY DUTY SAFETY SWITCHES
VISIBLE BLADE TYPE
400 AMPERE - SERIES E5
ENCLOSURE - NEMA TYPE 3R RAINPROOF (SUFFIX R)



DWG# 3453
NO.