



## Main

Product	Single Throw Safety Switch
Duty Rating	Heavy duty
Device application	Heavy application
Disconnect Type	Non-fusible disconnect
Factory Installed Neutral	None
Phase	3 phase
Number of Poles	6
Current Rating	200 A
Voltage Rating	600 V AC
Enclosure Rating	NEMA 3R/12 galvanized steel
Maximum Horse Power Rating	60 Hp 240 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 125 Hp 480 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52 150 hp 600 V at AC 50-60 Hz for 3 phase conforming to NEC 430.52

## Complementary

Mounting Type	Surface
Electrical Connection	Lugs
Wiring configuration	6-wire
Wire Size	AWG 6...250 kcmil copper or aluminium
Tightening torque	275 lbf.in (31.07 N.m) 0.02...0.20 in <sup>2</sup> (13.3...127 mm <sup>2</sup> ) (AWG 6...250 kcmil)
Depth	8.75 in (222.25 mm)
Width	24.88 in (631.95 mm)
Height	29 in (736.60 mm)
Net Weight	82.50 lb(US) (37.42 kg)

## Environment

Certifications	UL listed file E2875
----------------	----------------------

## Ordering and shipping details

Category	00116-H&HU SW,4&6P,N12,30-200A
Discount Schedule	DE1
GTIN	785901396765
Nbr. of units in pkg.	1
Package weight(Lbs)	72.00 lb(US) (32.659 kg)
Returnability	No
Country of origin	US

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	7.40 in (18.796 cm)
Package 1 width	17.10 in (43.434 cm)
Package 1 Length	26.30 in (66.802 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
PVC free	Yes

## Contractual warranty

Warranty	18 months
----------	-----------