



## Main

Product	Single Throw Safety Switch
Duty Rating	Light duty
Device application	Furnace Garages
Disconnect Type	Fusible disconnect
Factory Installed Neutral	Neutral (factory installed)
Phase	3 phase
Number of Poles	1
Current Rating	30 A
Voltage Rating	120 V AC
NEMA degree of protection	NEMA 1

## Complementary

Short-circuit current	10 kA
Fuse Type	Plug
Mounting Type	Surface
Wiring configuration	2-wire
Wire Size	AWG 14...AWG 8 copper AWG 12...AWG 8 aluminium
Tightening torque	30 Lbf.In (3.39 N.m) 0.00...0.01 in <sup>2</sup> (2.082...8.367 mm <sup>2</sup> ) (AWG 14...AWG 8) 30 lbf.in (3.39 N.m) 0.01...0.01 in <sup>2</sup> (3.307...8.367 mm <sup>2</sup> ) (AWG 12...AWG 8)
Depth	4 in (101.60 mm)
Width	6.13 in (155.70 mm)
Height	7.63 in (193.80 mm)

## Ordering and shipping details

Category	00057-LIGHT DUTY SW, NEMA1, 30A
Discount Schedule	DE1A
GTIN	785901115489
Nbr. of units in pkg.	1
Package weight(Lbs)	3.28 lb(US) (1.488 kg)
Returnability	Yes
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Package 1 Height	5.50 in (13.97 cm)
Package 1 width	6.40 in (16.256 cm)
Package 1 Length	8.60 in (21.844 cm)
Unit Type of Package 2	PAL
Number of Units in Package 2	200
Package 2 Weight	678.00 lb(US) (307.535 kg)
Package 2 Height	40.00 in (101.6 cm)
Package 2 width	40.00 in (101.6 cm)
Package 2 Length	48.00 in (121.92 cm)

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Toxic heavy metal free	Yes
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>

## Contractual warranty

Warranty	18 months
----------	-----------