



### Main

Product	Sealed Transformer
Certifications	UL Listed
Type	Mini Power-Zone
Enclosure Code	CC
Insulation Temperature	365 °F (185 °C)
Phase	3 phase
Primary Voltage	480 V
Secondary Voltage	208Y/120 V
Full Capacity Taps	2 5 % FCBN
Power Rating	22.5 kVA
Temperature Rise	115 °C
Winding Material	Copper
Interrupt Rating	18 kA
Circuit Breaker Type	Primary main breaker Secondary main breaker Feeder breaker
Interior Type	NQ Panelboard interior
Number of Spaces Available	24
Number of Circuits	24
Enclosure Type	NEMA 3R hot-rolled steel

### Ordering and shipping details

Category	16276-MPZ BOLT-ON BRANCH CB
Discount Schedule	PE2
GTIN	785901084341
Nbr. of units in pkg.	1
Package weight(Lbs)	670.00 lb(US) (303.907 kg)
Returnability	No
Country of origin	US

### Packing Units

Unit Type of Package 1	PCE
Package 1 Height	14.49 in (36.8 cm)
Package 1 width	29.13 in (74 cm)
Package 1 Length	51.26 in (130.2 cm)

### Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Nickel (Metallic), which is known to the State of California to cause cancer, and Bisphenol A (BPA), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes

---

China RoHS Regulation	<a href="#">China RoHS Declaration</a>
PVC free	Yes

---

### Contractual warranty

---

Warranty	18 months
----------	-----------

---