



## Main

Product	Surge protection device
Range	Surge Breaker QO

## Complementary

Surge Current	22.5 kA
Voltage Rating	120/240 V AC
Number of Phases	1 phase
Wiring Configuration	3-wire
MCOV	150 V 300 V
SCCR	22 kA
Local Signalling	1 LED green normal operation
Product destination	Load center QO
Height	3.7 in (93.98 mm)
Width	1.5 in (38.10 mm)
Depth	2.6 in (66.04 mm)

## Environment

Enclosure Rating	NEMA 2
Ambient Operating	149 °F (65 °C)

## Ordering and shipping details

Category	08461-SURGE PROTECTION RESI
Discount Schedule	DE1B
GTIN	785901210894
Returnability	Yes
Country of origin	MX

## Packing Units

Unit Type of Package 1	PCE
Package 1 Length	5.50 in (13.97 cm)
Number of Units in Package 1	1
Package 2 Width	6.60 in (16.764 cm)
Package 2 Height	6.10 in (15.494 cm)
Package 2 Weight	13.07 lb(US) (5.928 kg)
Package 1 Width	3.00 in (7.62 cm)
Package 1 Height	1.70 in (4.318 cm)
Package 1 Weight	10.40 oz (294.835 g)

Number of Units in Package 2	20
Unit Type of Package 2	CAR
Package 2 Length	16.70 in (42.418 cm)

### Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>

### Contractual warranty

Warranty	18 months
----------	-----------