



Main

| | |
|-----------------------|--------------------------------------|
| Product | Miniature circuit-breaker |
| Range | QO |
| Current Rating | 90 A |
| Voltage Rating | 120/240 V AC 240 V AC 120 V AC |
| Mounting Type | Bolt-on |
| Number of Poles | 2P |
| Circuit Breaker Type | Standard |
| Ratings | HACR rated |
| Electrical Connection | Box lugs |

Complementary

| | |
|------------------------|---|
| Interrupt Rating | 22 KA 120/240 V AC 50/60 Hz 22 KA 240 V AC 50/60 Hz 22 kA 120 V AC 50/60 Hz |
| Number of Panel Spaces | 2 |
| Wire Size | AWG 4...AWG 2/0 copper or aluminium |
| Tightening Torque | 40.71 lbf.in (4.6 N.m) |
| Height | 3.50 in (89 mm) |
| Width | 1.50 in (38 mm) |
| Depth | 2.91 in (74 mm) |
| Net Weight | 0.71 lb(US) (0.322 kg) |

Environment

| | |
|----------------|------------------|
| Certifications | UL Listed CSA |
| Ambient Rating | 104 °F (40 °C) |

Ordering and shipping details

| | |
|-----------------------|----------------------------|
| Category | 00015-QOB CIRCUIT BREAKERS |
| Discount Schedule | DE2 |
| GTIN | 785901120674 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 11.36 oz (322.051 g) |
| Returnability | Yes |
| Country of origin | MX |

Packing Units

| | |
|------------------------|---------------------|
| Unit Type of Package 1 | PCE |
| Package 1 Height | 1.50 in (3.81 cm) |
| Package 1 width | 3.40 in (8.636 cm) |
| Package 1 Length | 4.30 in (10.922 cm) |

Offer Sustainability

| | |
|-----------------------------|---|
| Sustainable offer status | Green Premium product |
| California proposition 65 | WARNING: This product can expose you to chemicals including: Cadmium and cadmium compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH Regulation | REACH Declaration |
| EU RoHS Directive | Compliant EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |
| China RoHS Regulation | China RoHS Declaration |
| Halogen content performance | Halogen free product |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|