

Meter socket, horizontal ganged, ringless socket, 360A, 4 position, 4 jaws, 600 VAC max, overhead/underground, no bypass

Main

Product Type	Meter Socket
Rated Current	360 A
Number of Meter Sockets	4
Number of Phases	1 phase
Rated Operational Voltage	600 V AC

Complementary

Number of Jaws	4 without jaw release
Bypass Type	No bypass
Meter Socket Type	Ringless
Certifications	UL Listed
Enclosure Rating	NEMA 3R
Box Number	18R
Wire Gauge	AWG 1/0...500 kcmil aluminium)main lugs AWG 1/0...500 kcmil copper)main lugs AWG 8...250 kcmil aluminium)branch lugs AWG 8...250 kcmil copper)branch lugs
Service Feed Location	UG OH
Wiring Configuration	3-wire
Hub Type	A-L ACPL closing plate
Height	14.12 in (358.65 mm)
Width	40.62 in (1031.75 mm)
Depth	5.38 in (136.65 mm)

Ordering and shipping details

Category	00039-METER SOCKETS & HUBS
Discount Schedule	DE4
GTIN	785901291251
Number of Units in Package 1	1
Package 1 Weight	47.74 lb(US) (21.655 kg)
Returnability	Yes
Country of origin	US

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	41.81 in (106.2 cm)
Package 1 Width	5.98 in (15.2 cm)
Package 1 Length	14.80 in (37.6 cm)

Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including: Nickel (Metallic), which is known to the State of California to cause cancer, and Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov
EU RoHS Directive	Under investigation

Contractual warranty

Warranty	18 months
----------	-----------