


Note:
 - Drawings Not To Scale
 - Drawings Subject to Change Without Notice
 - Dimensions are inches next to [Millimeters]

Part No.:

XCKD2106N12



Telemecanique Sensors
 1875 Founders Drive
 Dayton, OH 45420-4017
 Customer Care Center : 1-800-435-2121
 Web : www.tesensors.com

Technical Information:

Terminal Type: Screw Clamp
 Enclosure Rating: NEMA 1/2/4/6/12/13; IP66/67
 Approvals: UL # E164353 - CSA # 164581 - CE Marked
 Weight: 0.175 kg (0.386 lb)
 Conforming to Standards: CENELEC EN 50047
 RoHS: Yes
 Operating Temperature Range: -13 to 158 ° F
 Shock Resistance: 50G
 Vibration Resistance: 25G
 Max. Actuation Speed : 1 m/s
 Repeat Accuracy:
 Operating Torque/Force: 18.40 Inch-Ounces (0.13Nm)

Specification:

Description: XCKD Limit Switch Omnidirectional cat whisker
 Body Style/Type Description: IEC OsiSense Limit Switches XCKD Compact Modular 31mm Metal Body
 Head Type: ZCE06 Omnidirectional cat whisker
 Lever Arms:
 Body with Contact Type: ZCD21 2-pole N.O./N.C. snap action
 Conduit Thread: ZCDEN12 1/2" NPT
 Ampere Rating Continuous: 10A
 Maximum Voltage Rating: 240VAC/250VDC
 Actuation: Any Direction
 Actuator Action: Momentary
 Lever Arm Length:
 Roller Dimension:
 Roller Material:
 Contact Configuration: 1 N.O./1 N.C.
 Contact Operation: Snap Action
 Connection Type: Conduit Entrance (0.5 Inch NPT)
 Head Material: Zamak
 Positive Opening: No
 Cable Length: