


**Note:**  
 - Drawings Not To Scale  
 - Drawings Subject to Change Without Notice  
 - Dimensions are inches next to [Millimeters]

Part No.:  
**XCKT2110N12**



Telemecanique Sensors  
 1875 Founders Drive  
 Dayton, OH 45420-4017  
 Customer Care Center : 1-800-435-2121  
 Web : www.tesensors.com

Technical Information:	
Terminal Type:	Screw Clamp
Enclosure Rating:	NEMA 1/2/4/6/12/13; IP66/67
Approvals:	UL # E164353 - CSA # 164581 - CE Marked
Weight:	0.100 kg (0.220 lb)
Conforming to Standards:	CENELEC EN 50047
RoHS:	Yes
Operating Temperature Range:	-13 to 158 ° F
Shock Resistance:	50G
Vibration Resistance:	25G
Max. Actuation Speed :	0.5 m/s
Repeat Accuracy:	0.1 mm on the tripping points
Operating Torque/Force:	133 Inch-Pounds (15Nm)

Specification:	
Description:	XCKT Limit Switch Metal end plunger
Body Style/Type Description:	IEC OsiSense Limit Switches XCKT Compact Modular 58mm Plastic Body
Head Type:	ZCE10 Metal end plunger
Lever Arms:	
Body with Contact Type:	ZCT21 2-pole N.O./N.C. Snap Action
Conduit Thread:	1/2" NPT
Ampere Rating Continuous:	10A
Maximum Voltage Rating:	240VAC/250VDC
Actuation:	Vertical
Actuator Action:	Momentary
Lever Arm Length:	
Roller Dimension:	
Roller Material:	
Contact Configuration:	1 N.O./1 N.C.
Contact Operation:	Snap Action
Connection Type:	Conduit Entrance (0.5 Inch NPT)
Head Material:	Zamak
Positive Opening:	Yes
Cable Length:	