

XCSPL563

Guard switch, Telemecanique Safety switches
XCS, XCSPL, straight lever, to right or to left,
1NC+1 NO -1/2"NPT

Main

| | |
|--------------------------------|---|
| Range of Product | Telemecanique Safety switches XCS |
| Product or Component Type | Guard switch |
| Component name | XCSPL |
| Material | Plastic |
| Head type | Turret head rotary lever |
| Insulation | Double insulated |
| Type of operator | Straight lever |
| Operator direction information | To right or to left |
| Electrical Connection | Terminal |
| Contacts type and composition | 1 NC + 1 NO |
| Contact operation | Slow-break, break before make |
| Clamping connection capacity | 1 x 0.5...2 x 1.5 mm ² with or without cable end |
| Cable entry | 1 entry tapped 1/2" NPT |
| Number of poles | 2 |

Complementary

| | |
|--|--|
| Cable outer diameter | 0.3...0.4 in (7...10 mm) |
| Positive opening | With NC contact |
| Tripping angle | 5 ° |
| Mechanical durability | 1000000 cycles |
| Minimum torque for tripping | 0.9 lbf.in (0.1 N.m) |
| Positive opening minimum torque | 2.21 lbf.in (0.25 N.m) |
| Contact code designation | A300, AC-15 (Ue = 120 V, Ie = 6 A)EN/IEC 60947-5-1 A300, AC-15 (Ue = 240 V, Ie = 3 A)EN/IEC 60947-5-1 Q300, DC-13 (Ue = 125 V, Ie = 0.55 A)EN/IEC 60947-5-1 Q300, DC-13 (Ue = 250 V, Ie = 0.27 A)EN/IEC 60947-5-1 |
| [Ithe] conventional enclosed thermal current | 10 A |
| [Ui] rated insulation voltage | 300 VUL 508 300 VCSA C22.2 No 14 500 V 3)EN/IEC 60947-1 |
| [Uimp] rated impulse withstand voltage | 6 kV EN/IEC 60947-5-1 |
| Maximum resistance across terminals | 30 mOhm EN/IEC 60947-5-4 |
| Short-circuit protection | 10 A cartridge fuse gG (gl) |
| Safety level | Can reach category 4 with the appropriate monitoring system and correctly wired EN/ISO 13849-1 Can reach PL = e with the appropriate monitoring system and correctly wired EN/ISO 13849-1 Can reach SIL 3 with the appropriate monitoring system and correctly wired IEC 61508 |
| Safety reliability data | B10d = 5000000 value given for a life time of 20 years limited by mechanical or contact wear |
| Enclosure Material | Polyamide PA66 fibre glass impregnated |
| Lever material | Stainless steel |
| Width | 4.06 in (103 mm) |
| Height | 3.5 in (88 mm) |
| Depth | 1.2 in (30 mm) |
| Net Weight | 0.209 lb(US) (0.095 kg) |

Environment

| | |
|---------------------------------------|--|
| Standards | EN/ISO 12100 EN/IEC 60947-5-4 EN 1088/ISO 14119 EN/IEC 60204-1 CSA C22.2 No 14 EN/IEC 60947-5-1 UL 508 |
| Product Certifications | UL[RETURN]CSA[RETURN]BG |
| Protective treatment | TH TC |
| Ambient Air Temperature for Operation | -13...158 °F (-25...70 °C) |
| Ambient Air Temperature for Storage | -40...158 °F (-40...70 °C) |
| Vibration resistance | 50 gn 10...500 Hz)IEC 60068-2-6 |
| Shock resistance | 50 gn 11 ms IEC 60068-2-27 |
| Electrical shock protection class | Class II EN/IEC 61140 |
| IP degree of protection | IP67 conforming to IEC 60529 |

Ordering and shipping details

| | |
|-------------------|---------------|
| Category | US1000T22411 |
| Discount Schedule | 000T |
| GTIN | 3389110866469 |
| Returnability | Yes |
| Country of origin | US |

Packing Units

| | |
|------------------------------|-------------------|
| Unit Type of Package 1 | PCE |
| Number of Units in Package 1 | 1 |
| Package 1 Height | 1.26 in (3.2 cm) |
| Package 1 Width | 7.87 in (20.0 cm) |
| Package 1 Length | 1.50 in (3.8 cm) |
| Package 1 Weight | 4.4 oz (125.0 g) |

Offer Sustainability

| | |
|----------------------------|---|
| California proposition 65 | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
| REACH free of SVHC | Yes |
| EU RoHS Directive | Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration |
| Mercury free | Yes |
| RoHS exemption information | Yes |

Contractual warranty

| | |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|