

# XS1N05PA311S

Inductive proximity sensors XS, inductive sensor XS1 M5, L42mm, stainless, Sn0.8mm, 5..24VDC, M8

## Main

|                                    |   |
|------------------------------------|---|
| Range of Product                   | Telemecanique Inductive proximity sensors XS    |
| Series name                        | General purpose                                 |
| Sensor Type                        | Inductive proximity sensor                      |
| Device Application                 | -   |
| Sensor name                        | XS1   |
| Sensor design                      | Cylindrical M5                                  |
| Size                               | 42 mm   |
| Body type                          | Fixed   |
| Detector flush mounting acceptance | Flush mountable                                 |
| Material                           | Stainless steel                                 |
| Type of output signal              | Discrete  |
| Wiring Technique                   | 3-wire  |
| [Sn] nominal sensing distance      | 0.03 in (0.8 mm)                                |
| Discrete output function           | 1 NO  |
| Output circuit type                | DC  |
| Discrete output type               | PNP   |
| Electrical connection              | Male connector M8, 3 pins                       |
| [Us] rated supply voltage          | 5...24 V DC                                     |
| Switching capacity in mA           | <= 100 mA overload and short-circuit protection |
| IP degree of protection            | IP67 conforming to IEC 60529                    |

## Complementary

|                        |                                     |
|------------------------|-------------------------------------|
| Thread type            | M5 x 0.5                            |
| Detection face         | Frontal                             |
| Front material         | PPS                                 |
| Enclosure Material     | Stainless steel 303                 |
| Operating zone         | 0.0000000000...0.02 in (0...0.6 mm) |
| Status LED             | Output state 1 LED yellow)          |
| Supply voltage limits  | 5...30 V DC                         |
| Switching frequency    | <= 5000 Hz                          |
| Maximum voltage drop   | <2 V closed)                        |
| Current consumption    | <= 10 mA no-load                    |
| Maximum delay first up | 5 ms                                |
| Maximum delay response | 1 ms                                |
| Maximum delay recovery | 1 ms                                |
| Marking                | CE                                  |
| Threaded length        | 0.9 in (24 mm)                      |
| Length                 | 1.7 in (42 mm)                      |
| Net Weight             | 0.033 lb(US) (0.015 kg)             |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

## Environment

|                                       |   |
|---------------------------------------|---|
| Product Certifications                | UL[RETURN]CSA                           |
| Ambient Air Temperature for Operation | -13...158 °F (-25...70 °C)              |
| Ambient Air Temperature for Storage   | -40...185 °F (-40...85 °C)              |
| Vibration resistance                  | 25 gn +/- 2 mm 10...55 Hz)IEC 60068-2-6 |
| Shock resistance                      | 50 gn 11 ms IEC 60068-2-27              |



## Ordering and shipping details

|                   |               |
|-------------------|---------------|
| Category          | US10DS222486  |
| Discount Schedule | 0DS2          |
| GTIN              | 3389110925685 |
| Returnability     | Yes           |
| Country of origin | MX            |

## Packing Units

|                              |                       |
|------------------------------|-----------------------|
| Unit Type of Package 1       | PCE                   |
| Number of Units in Package 1 | 1                     |
| Package 1 Height             | 1.61 in (4.100 cm)    |
| Package 1 Width              | 3.74 in (9.500 cm)    |
| Package 1 Length             | 2.56 in (6.500 cm)    |
| Package 1 Weight             | 0.423 oz (12.000 g)   |
| Unit Type of Package 2       | S02                   |
| Number of Units in Package 2 | 44                    |
| Package 2 Height             | 5.91 in (15 cm)       |
| Package 2 Width              | 11.81 in (30 cm)      |
| Package 2 Length             | 15.75 in (40 cm)      |
| Package 2 Weight             | 29.841 oz (846.000 g) |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| SCIP Number                | 3bc2f5da-1620-4d53-878c-410a857f3212  |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)  |
| Mercury free               | Yes   |
| RoHS exemption information |  Yes   |
| Circularity Profile        |  <a href="#">End Of Life Information</a>   |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|