

# XY2CE1A250

Latching emergency stop rope pull switch, Telemecanique rope pull switches XY2C, e XY2CE, RH side -1NC+1 NO, booted pushbutton

## Main

|                           |  |
|---------------------------|--|
| Range of Product          | Telemecanique Emergency stop rope pull switches XY2C |
| Product or Component Type | Latching emergency stop rope pull switch             |
| Device short name         | XY2CE  |
| Housing colour            | Red RAL 3000   |
| Overvoltage category      | Class I EN/IEC 61140<br>Class I NF C 20-030          |

## Complementary

|  |   |
|--|---|
| Local signalling                             | Without pilot light   |
| Number of cables                             | 1   |
| Trigger cable maximum length                 | 229.7 ft (70 m)   |
| Body Material                                | Zamak   |
| Cover Material                               | Stainless steel   |
| Reset  | By booted push-button   |
| Contacts type and composition                | 1 NC + 1 NO   |
| Contact operation                            | Slow-break  |
| Trigger cable anchor point                   | RH side   |
| Connections - terminals                      | Screw clamp terminal, 1 x 0.5...2 x 1.5 mm <sup>2</sup>   |
| Tightening torque                            | 7.08...10.6 lbf.in (0.8...1.2 N.m)  |
| Cable entry number                           | 3 plain hole Pg 13.5 or ISO M20 cable gland   |
| Safety level                                 | Can reach PL = e with the appropriate monitoring system and correctly wired EN/ISO 13849-1<br>Can reach category 4 with the appropriate monitoring system and correctly wired EN/ISO 13849-1<br>Can reach SIL 3 with the appropriate monitoring system and correctly wired EN/IEC 61508 |
| Safety reliability data                      | B10d = 300000 value given for a life time of 20 years limited by mechanical or contact wear IEC 60947-5-5   |
| Marking                                      | CE  |
| Mechanical durability                        | 60000 cycles  |
| Distance between cable supports              | 16.4 ft (5 m)   |
| [Ie] rated operational current               | 3 A 240 V, AC-15, A300 EN/IEC 60947-5-1 appendix A<br>0.27 A 250 V, DC-13, Q300 EN/IEC 60947-5-1 appendix A   |
| [Ithe] conventional enclosed thermal current | 10 A  |
| [Ui] rated insulation voltage                | 500 V 3)EN/IEC 60947-1<br>300 VUL 508<br>300 VCSA C22.2 No 14   |
| [Uimp] rated impulse withstand voltage       | 6 kV EN/IEC 60947-1   |
| Positive opening                             | With EN/IEC 60947-5-1   |
| Maximum resistance across terminals          | 25 MOhm EN/IEC 60255-7 category 3<br>25 MOhm NF C 93-050 method A   |
| Short-circuit protection                     | 10 A cartridge fuse gG EN/IEC 60269   |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

|                               |                        |
|-------------------------------|------------------------|
| Terminals description ISO n°1 | (13-14)NO<br>(21-22)NC |
| Net Weight                    | 3.20 lb(US) (1.45 kg)  |
| Compatibility code            | XY2CE                  |

## Environment

|                                       |   |
|---------------------------------------|---|
| Standards                             | CSA C22.2 No 14<br>EN/IEC 60947-5-1<br>EN/IEC 60947-5-5<br>UL 508<br>EN/ISO 13850<br>Work equipment directive 2009/104/EC<br>EN/IEC 60204-1<br>Machinery directive 2006/42/EC |
| Product certifications                | UL category NISD emergency stop devices<br>CSA<br>CCC   |
| Protective treatment                  | TC  |
| Ambient Air Temperature for Operation | -13...158 °F (-25...70 °C)  |
| Ambient Air Temperature for Storage   | -40...158 °F (-40...70 °C)  |
| Vibration resistance                  | 10 gn 10...300 Hz)EN/IEC 60068-2-6  |
| Shock resistance                      | 50 gn 11 ms EN/IEC 60068-2-27   |
| IP degree of protection               | IP66 IEC 60529  |


## Ordering and shipping details

|                   |               |
|-------------------|---------------|
| Category          | US1000T22441  |
| Discount Schedule | 000T          |
| GTIN              | 3389110318609 |
| Returnability     | Yes           |
| Country of origin | US            |

## Packing Units

|                              |                            |
|------------------------------|----------------------------|
| Unit Type of Package 1       | PCE                        |
| Number of Units in Package 1 | 1                          |
| Package 1 Height             | 3.54 in (9.000 cm)         |
| Package 1 Width              | 6.30 in (16.000 cm)        |
| Package 1 Length             | 7.87 in (20.000 cm)        |
| Package 1 Weight             | 3.391 lb(US) (1.538 kg)    |
| Unit Type of Package 2       | S03                        |
| Number of Units in Package 2 | 6                          |
| Package 2 Height             | 11.81 in (30.000 cm)       |
| Package 2 Width              | 11.81 in (30.000 cm)       |
| Package 2 Length             | 15.75 in (40.000 cm)       |
| Package 2 Weight             | 21.522 lb(US) (9.762 kg)   |
| Unit Type of Package 3       | P06                        |
| Number of Units in Package 3 | 48                         |
| Package 3 Height             | 29.53 in (75.000 cm)       |
| Package 3 Width              | 23.62 in (60.000 cm)       |
| Package 3 Length             | 31.50 in (80.000 cm)       |
| Package 3 Weight             | 195.550 lb(US) (88.700 kg) |

## Offer Sustainability

|                            |   |
|----------------------------|---|
| SCIP Number                | 7bb93ca0-de96-486f-af69-233ea6279d10  |
| California proposition 65  | WARNING: This product can expose you to chemicals including: Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a> |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)  |
| Mercury free               | Yes   |
| RoHS exemption information |  Yes   |
| Circularity Profile        | No need of specific recycling operations  |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|